



GREEN POWER GP220S-P-N SOUNDPREOF

Product price:

26,456.00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

You can choose from several versions:

-Silenced group with AVR-Leroy alternator (automatic control pack)

-Silenced group with high AVR-Mecc alternator (automatic control unit)

-Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 176

Continuous power three phase (KW): 160

Maximum power three phase (KVA): 220

Continuous power three phase (KVA): 200

Fuel: Diesel



Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: PERKINS 1106A-70TAG4, 4 stroke turbo-aftercooler

Emissions Regulations: NON EMISSIONATO

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Elettrico

Engine capacity (cm³): 7010

Number cylinders: 6

Cylinders' position: In line

Cooling: Water

Alternator: MECC ALTE ECO38-2S/4 - Sincrono

Poles: 4

Protection degree: IP23

Fuel tank capacity (L): 170

Consumption (L/h): 24.7 Lt/h al 75% del carico

Running time (h): 5.06 h al 75% del carico

Acoustic pressure: 70 dB(A)

Length (mm): 3300

Width (mm): 1100

Height (mm): 1770

Dry weight (Kg): 2140

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

