



# GREEN POWER GP250A-P-N OPEN

**Product price:**

**25.490,00 € tax excluded**

## **Product description:**

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

## **Product features:**

Phase: Three phase

Maximum power three phase (KW): 202.4

Continuous power three phase (KW): 184

Maximum power three phase (KVA): 253

Continuous power three phase (KVA): 230

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: 1506A-E88TAG2

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 8800



Number cylinders: 6

Cylinders' position: In line

Cooling: Water

Alternator: LINZ PRO 22SD/4 - Sincrono

Poles: 4

Fuel tank capacity (L): 150

Consumption (L/h): 24.7 Lt/h al 75% del carico

Running time (h): 9.62 h al 75% del carico

Length (mm): 3000

Width (mm): 1100

Height (mm): 1500

Dry weight (Kg): 1730

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: AVR

