



GREEN POWER GP280S-P-N SOUNDPREOF

Product price:

33,076.00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

You can choose from several versions:

- Silenced group with AVR-Leroy alternator (automatic control pack)
- Silenced group with high AVR-Mecc alternator (automatic control unit)
- Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 220

Continuous power three phase (KW): 200

Maximum power three phase (KVA): 275

Continuous power three phase (KVA): 250

Fuel: Diesel



Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: Perkins 1206A-E70TTAG3
Emissions Regulations: NON EMISSIONATO
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Elettrico
Engine capacity (cm³): 7010
Number cylinders: 6
Cylinders' position: In line
Cooling: Water
Alternator: MECC ALTE ECO38-1L/4 - Sincrono
Poles: 4
Protection degree: IP23
Fuel tank capacity (L): 170
Consumption (L/h): 41.6 Lt/h al 75% del carico
Running time (h): 3.61 h al 75% del carico
Acoustic pressure: 70 dB(A)
Length (mm): 3300
Width (mm): 1100
Height (mm): 1770
Dry weight (Kg): 2510
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR

