



GREEN POWER GP560S-P SOUNDPROOF

Product price:

59,177.00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

You can choose from several versions:

- -Silenced group with AVR-Leroy alternator (automatic control pack)
- -Silenced group with high AVR-Mecc alternator (automatic control unit)
- -Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 440 Continuous power three phase (KW): 400 Maximum power three phase (KVA): 550 Continuous power three phase (KVA): 500

Fuel: Diesel



Frequency (Hz): 50 Voltage (V): 230 / 400

Engine: Perkins 2506A-E15TAG2

Emissions Regulations: NON EMISSIONATO

Engine rpm (rpm): 1500 Speed governor: Electronic Starting system: Elettrico Engine capacity (cm³): 15200

Number cylinders: 6 Cylinders' position: In line

Cooling: Water

Alternator: MECC ALTE ECO40-3S/4

Poles: 4

Protection degree: IP23 Fuel tank capacity (L): 260

Consumption (L/h): 81 Lt/h al 75% del carico Running time (h): 3.7 h al 75% del carico

Acoustic pressure: 69 dB(A)

Length (mm): 4500 Width (mm): 1450 Height (mm): 2190 Dry weight (Kg): 4840

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR