

# GREEN POWER GP610SM-P-N SOUNDPROOF

Product price:

# 72.830,00 € tax excluded

## **Product description:**

Ì

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

### You can choose from several versions:

-Silenced group with AVR-Leroy alternator (automatic control pack)

-Silenced group with high AVR-Mecc alternator (automatic control unit)

-Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.

### Product features:

Phase: Three phase Maximum power three phase (KW): 484 Continuous power three phase (KW): 440 Maximum power three phase (KVA): 605

PrestaShop

R

Continuous power three phase (KVA): 550 Fuel: Diesel Frequency (Hz): 50 Voltage (V): 230 / 400 Engine: PERKINS 2806A-E18TAG1A **Emissions Regulations: NON EMISSIONATO** Engine rpm (rpm): 1500 Speed governor: Electronic Starting system: Elettrico Engine capacity (cm<sup>3</sup>): 18130 Number cylinders: 6 Cylinders' position: In line Cooling: Water Alternator: LINZ PRO 22SD/4 - Sincrono Poles: 4 Protection degree: IP23 Fuel tank capacity (L): 310 Consumption (L/h): 90 Lt/h al 75% del carico Running time (h): 3.54 h al 75% del carico Acoustic pressure: 69 dB(A) Length (mm): 5000 Width (mm): 1900 Height (mm): 2350 Dry weight (Kg): 6200 Silenced: Yes Super silenced: Yes ATS Switch device : Optional Voltage regulator: AVR

R

Ø.