



# GREEN POWER GP880SM-P SOUNDPROOF

# Product price:

101,020.00 € tax excluded

# **Product description:**

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

### You can choose from several versions:

- -Silenced group with AVR-Leroy alternator (automatic control pack)
- -Silenced group with high AVR-Mecc alternator (automatic control unit)
- -Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.

## **Product features:**

Phase: Three phase

Maximum power three phase (KW): 704 Continuous power three phase (KW): 640 Maximum power three phase (KVA): 880 Continuous power three phase (KVA): 800

Fuel: Diesel



Frequency (Hz): 50 Voltage (V): 230 / 400

Engine: Perkins 4006-23TAG3A

Emissions Regulations: NON EMISSIONATO

Engine rpm (rpm): 1500 Speed governor: Electronic Starting system: Elettrico Engine capacity (cm³): 22921

Number cylinders: 6 Cylinders' position: In line

Cooling: Water

Alternator: LINZ PRO 22SD/4 - Sincrono

Poles: 4

Protection degree: IP23 Fuel tank capacity (L): 350

Consumption (L/h): 130 Lt/h al 75% del carico

Running time (h): 4 at 75% of the load

Acoustic pressure: 69 dB(A)

Length (mm): 5850 Width (mm): 1900 Height (mm): 2350 Dry weight (Kg): 8100

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR