



# GREEN POWER GP1650A/P OPEN (MANUAL CONTROL UNIT)

**Product price:**

**200,836.00 € tax excluded**

**Product description:**

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

**THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION**

**You can choose between the versions:**

- Open group with AVR-Leroy alternator (automatic power pack)
- Open group with AVR-Mecc Alte alternator (automatic power pack)
- Open group with AVR-Stamford alternator (automatic power pack)

The image is purely indicative.



---

**Product features:**

Phase: Three phase  
Maximum power three phase (KW): 1320  
Continuous power three phase (KW): 1200  
Maximum power three phase (KVA): 1650  
Continuous power three phase (KVA): 1500  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: 1506A-E88TAG2  
Emissions Regulations: NON EMISSIONATO  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 45842  
Number cylinders: 12  
Cylinders' position: In line  
Cooling: Water  
Alternator: LINZ PRO 22SD/4 - Sincrono  
Poles: 4  
Protection degree: IP23  
Fuel tank capacity (L): 800  
Consumption (L/h): 237 Lt/h al 75% del carico  
Running time (h): 3.37 h al 75% del carico  
Length (mm): 5200  
Width (mm): 2200  
Height (mm): 2500  
Dry weight (Kg): 12000  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: AVR

