



GREEN POWER GP88A/I-N OPEN (MANUAL CONTROL UNIT)



Product price:

8,791.00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 70.4

Continuous power three phase (KW): 64

Maximum power three phase (KVA): 88

Continuous power three phase (KVA): 80

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: FPT N45SM2A

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 4500



Number cylinders: 4

Cylinders' position: In line

Cooling: Water

Alternator: Linz PRO22SB/4, synchronous, brushless

Poles: 4

Fuel tank capacity (L): 100

Consumption (L/h): 12.7 al 75% del carico

Running time (h): 9.62 h al 75% del carico

Length (mm): 2100

Width (mm): 900

Height (mm): 1300

Dry weight (Kg): 1180

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: AVR

