



GREEN POWER GP190S/IN SOUNDPROOF (MANUAL CONTROL UNIT)

Product price:

19.364,00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 165

Continuous power three phase (KW): 136

Maximum power three phase (KVA): 198

Continuous power three phase (KVA): 170

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: FPT N67TM4

Emissions Regulations: Not Emitted

Engine rpm (rpm): 1500



Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 6
Number cylinders: 6
Cylinders' position: In line
Cooling: Water
Alternator: LINZ PRO 22SD/4 - Sincrono
Poles: 4
Fuel tank capacity (L): 125
Consumption (L/h): 24.7 Lt/h al 75% del carico
Running time (h): 9.62 h al 75% del carico
Acoustic pressure: 70 dB(A)
Length (mm): 3300
Width (mm): 1100
Height (mm): 1770
Dry weight (Kg): 1730
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR

