



GREEN POWER GP610A/I OPEN (MANUAL CONTROL UNIT)

Product price:

53,513.00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 484 Continuous power three phase (KW): 440 Maximum power three phase (KVA): 605 Continuous power three phase (KVA): 550

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400 Engine: FPT CR16 TE1W

Emissions Regulations: NON EMISSIONATO

Engine rpm (rpm): 1500 Speed governor: Electronic Starting system: Elettrico



Engine capacity (cm³): 15900

Number cylinders: 6

Cylinders' position: In line

Cooling: Water

Alternator: MECC ALTE ECO40-1L/4

Poles: 4

Protection degree: IP23 Fuel tank capacity (L): 340

Consumption (L/h): 84.5 Lt/h al 75% del carico

Running time (h): 4 h al 75% del carico

Length (mm): 3400 Width (mm): 1400 Height (mm): 2200 Dry weight (Kg): 3430

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: AVR