



# GREEN POWER GP700A/C OPEN (MANUAL CONTROL UNIT)

**Product price:**

**80.441,00 € tax excluded**

## **Product description:**

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

## **Product features:**

Phase: Three phase

Maximum power three phase (KW): 560

Continuous power three phase (KW): 508.8

Maximum power three phase (KVA): 700

Continuous power three phase (KVA): 636

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: CUMMINSVTA28G5

Emissions Regulations: NON EMISSIONATO

Engine rpm (rpm): 1500



Speed governor: Electronic  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 28000  
Number cylinders: 12  
Cylinders' position: In line  
Cooling: Water  
Alternator: MECC ALTEECO40 2L/4  
Poles: 4  
Protection degree: IP23  
Fuel tank capacity (L): 340  
Consumption (L/h): 104 Lt/h al 75% del carico  
Running time (h): 9.62 h al 75% del carico  
Length (mm): 3500  
Width (mm): 1600  
Height (mm): 2100  
Dry weight (Kg): 3430  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: AVR