



GREEN POWER GP1000A/C OPEN (MANUAL CONTROL UNIT)

Product price:

104.855,00 € tax excluded

Product description:

GREEN POWER GP1000A/C OPEN (MANUAL CONTROL UNIT)

Discover the GREEN POWER GP1000A/C in its open design, equipped with a manual control unit for precise and hands-on operation. This model represents GREEN POWER's commitment to delivering performance with the advantage of manual control, ensuring flexibility and reliability in a variety of applications. Its open configuration allows for easy installation and maintenance, making it an essential tool for those demanding peak efficiency. The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

Product features:

Phase: Three phase



Maximum power three phase (KW): 396
Continuous power three phase (KW): 480
Maximum power three phase (KVA): 495
Continuous power three phase (KVA): 600
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: 1506A-E88TAG2
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Electric
Engine capacity (cm³): 8800
Number cylinders: 12
Cylinders' position: In line
Cooling: Water
Alternator: LINZ PRO 22SD/4 - Sincrono
Poles: 4
Fuel tank capacity (L): 400
Consumption (L/h): 24.7 Lt/h al 75% del carico
Running time (h): 9.62 h al 75% del carico
Length (mm): 4500
Width (mm): 2050
Height (mm): 2350
Dry weight (Kg): 3430
Silenced: No
Super silenced: No
ATS Switch device : Optional
Voltage regulator: AVR

