



# GREEN POWER GP1000A/C OPEN (MANUAL CONTROL UNIT)

**Product price:**

**122.296,00 € tax excluded**

**Product description:**

GREEN POWER GP1000A/C OPEN (MANUAL CONTROL UNIT)

Discover the GREEN POWER GP1000A/C in its open design, equipped with a manual control unit for precise and hands-on operation. This model represents GREEN POWER's commitment to delivering performance with the advantage of manual control, ensuring flexibility and reliability in a variety of applications. Its open configuration allows for easy installation and maintenance, making it an essential tool for those demanding peak efficiency. The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

**THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION**

**You can choose between the versions:**

-Open group with AVR-Leroy alternator (automatic power pack)



- Open group with AVR-Mecc Alte alternator (automatic power pack)
- Open group with AVR-Stamford alternator (automatic power pack)

The image is purely indicative.

**Product features:**

Phase: Three phase

Maximum power three phase (KW): 800

Continuous power three phase (KW): 728

Maximum power three phase (KVA): 1000

Continuous power three phase (KVA): 910

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: CUMMINS KTA38G3

Emissions Regulations: Non Emissionati

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Elettrico

Engine capacity (cm<sup>3</sup>): 37800

Number cylinders: 12

Cylinders' position: In line

Cooling: Water

Alternator: MECC ALTE ECO43 2S/4

Poles: 4

Protection degree: IP23

Fuel tank capacity (L): 400

Consumption (L/h): 24.7 Lt/h al 75% del carico

Running time (h): 2.64 h al 75% del carico

Length (mm):

Width (mm): 2050

Height (mm): 2350

Dry weight (Kg): 3430

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: AVR

