



# GREEN POWER GP11A/KW-C OPEN (MANUAL CONTROL UNIT)

**Product price:**

**5.688,00 € tax excluded**

**Product description:**

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

**THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION**

**You can choose between the versions:**

- Open group with Compound-Linz alternator (automatic control unit)
- Open group with AVR-Leroy alternator (automatic power pack)
- Open group with AVR-Mecc Alte alternator (automatic power pack)
- Open genset with AVR-Stamford alternator (automatic power pack)

The image is purely indicative.



---

**Product features:**

Phase: Three phase

Maximum power three phase (KW): 8.8

Continuous power three phase (KW): 8

Maximum power three phase (KVA): 11

Continuous power three phase (KVA): 10

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+T CEE - 1 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: KOHLERKDW1404

Emissions Regulations: Non Emissionati

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm<sup>3</sup>): 1372

Number cylinders: 4

Cylinders' position: In line

Cooling: Water

Alternator: Linz E1S13SB/4, synchronous, with brushes

Poles: 4

Protection degree: IP21

Fuel tank capacity (L): 55

Consumption (L/h): 2.9 al 75% del carico

Running time (h): 19 at 75% of the load

Length (mm): 1300

Width (mm): 700

Height (mm): 1000

Dry weight (Kg): 380

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: Compound / AVR (optional)

