



GREEN POWER GP440S/DO-N SOUNDPROOF (MANUAL CONTROL UNIT)

Product price:

42.622,00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION

You can choose from several versions:

- -Silenced group with AVR-Leroy alternator (automatic power pack)
- -Silenced group with high AVR-Mecc alternator (automatic control unit)
- -Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.





Product features:

Phase: Three phase

Maximum power three phase (KW): 352 Continuous power three phase (KW): 320 Maximum power three phase (KVA): 440 Continuous power three phase (KVA): 400

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400 Engine: 1506A-E88TAG2

Emissions Regulations: Non Emissionati

Engine rpm (rpm): 1500 Speed governor: Electronic Starting system: Elettrico Engine capacity (cm³): 14618

Number cylinders: 8 Cylinders' position: In line

Cooling: Water

Alternator: MECC ALTEECO40 1S/4

Poles: 4

Fuel tank capacity (L): 410

Consumption (L/h): 24.7 Lt/h al 75% del carico Running time (h): 9.62 h al 75% del carico

Acoustic pressure: 69 dB(A)

Length (mm): 4300 Width (mm): 1600 Height (mm): 2300 Dry weight (Kg): 3630

Silenced: Yes

Super silenced: Yes

ATS Switch device: Optional

Voltage regulator: AVR