



GREEN POWER GP505A/DO-N OPEN (MANUAL CONTROL UNIT)

Product price:

37.808,00 € tax excluded

Product description:

GREEN POWER GP505A/DO-N OPEN (MANUAL CONTROL UNIT)

Introducing the GREEN POWER GP505A/DO-N, an open-design generator equipped with a manual control unit. This model is tailor-made for those who value direct control and hands-on operation. Combining power with user-centric design, the GP505A/DO-N ensures a seamless power supply while offering an intuitive interface for easy management. As with all GREEN POWER products, this unit is a testament to the brand's commitment to quality and innovation. The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION

You can choose between the versions:

-Open group with AVR-Leroy alternator (automatic power pack)



- Open group with AVR-Mecc Alte alternator (automatic power pack)
- Open genset with AVR-Stamford alternator (automatic power pack)

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 400

Continuous power three phase (KW): 360

Maximum power three phase (KVA): 500

Continuous power three phase (KVA): 450

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: 1506A-E88TAG2

Emissions Regulations: Non Emissionati

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Elettrico

Engine capacity (cm³): 14618

Number cylinders: 8

Cylinders' position: In line

Cooling: Water

Alternator: MECC ALTEECO40-2S/4

Poles: 4

Fuel tank capacity (L): 290

Consumption (L/h): 72.9 Lt/h al 75% del carico

Running time (h): 9.62 h al 75% del carico

Length (mm): 3200

Width (mm): 1300

Height (mm): 1900

Dry weight (Kg): 3430

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: AVR