



GREEN POWER GP385A/V OPEN (MANUAL CONTROL UNIT)

Product price:

35.636,00 € tax excluded

Product description:

GREEN POWER GP385A/V OPEN (MANUAL CONTROL UNIT)

Discover the GREEN POWER GP385A/V in its open design, equipped with a manual control unit for enhanced precision and control. This unit seamlessly combines power with flexibility, allowing for hands-on, intuitive management tailored to individual requirements. Reflecting GREEN POWER's commitment to top-notch quality and performance, this product stands as a testament to engineering excellence. The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION

You can choose between the versions:

-Open group with AVR-Leroy alternator (automatic power pack)



- Open group with AVR-Mecc Alte alternator (automatic power pack)
- Open genset with AVR-Stamford alternator (automatic power pack)

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 308

Continuous power three phase (KW): 280

Maximum power three phase (KVA): 385

Continuous power three phase (KVA): 350

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: VOLVOTAD1342GE

Emissions Regulations: Stage 2

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Elettrico

Engine capacity (cm³): 12780

Number cylinders: 6

Cylinders' position: In line

Cooling: Water

Alternator: LINZ PRO 22SD/4 - Sincrono

Poles: 4

Fuel tank capacity (L): 188

Consumption (L/h): 54 Lt/h al 75% del carico

Running time (h): 9.62 h al 75% del carico

Length (mm): 3200

Width (mm): 1100

Height (mm): 1900

Dry weight (Kg): 2720

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: AVR

