



# GREEN POWER GP33A/D OPEN (MANUAL CONTROL UNIT)

**Product price:**

**9,216.00 € tax excluded**

## **Product description:**

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

**THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION**

## **You can choose between the versions:**

- Open group with AVR-Leroy alternator (automatic power pack)
- Open group with AVR-Mecc Alte alternator (automatic power pack)
- Open genset with AVR-Stamford alternator (automatic power pack)

The image is purely indicative.

## **Product features:**

Phase: Three phase



---

Maximum power three phase (KW): 26.4  
Continuous power three phase (KW): 24  
Maximum power three phase (KVA): 33  
Continuous power three phase (KVA): 30  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: Deutz F4M2011, 4 stroke  
Emissions Regulations: Stage 2  
Engine rpm (rpm): 1500  
Speed governor: Mechanical  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 3108  
Number cylinders: 4  
Cylinders' position: In line  
Cooling: Water  
Alternator: Linz PRO18SC/4, synchronous, brushless  
Poles: 4  
Fuel tank capacity (L): 70  
Consumption (L/h): 5.4 al 75% del carico  
Running time (h): 12.96 h al 75% del carico  
Length (mm): 1750  
Width (mm): 700  
Height (mm): 1125  
Dry weight (Kg): 350  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: AVR

