



# GREEN POWER GP84S/D SOUNDPROOF (MANUAL CONTROL UNIT)

**Product price:**

**15,730.00 € tax excluded**

## **Product description:**

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

## **Product features:**

Phase: Three phase

Maximum power three phase (KW): 64.8

Continuous power three phase (KW): 60

Maximum power three phase (KVA): 81

Continuous power three phase (KVA): 75

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: DEUTZBF4M 2012C

Emissions Regulations: Stage 2

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Elettrico



---

Engine capacity (cm³): 4038  
Number cylinders: 4  
Cylinders' position: In line  
Cooling: Water  
Alternator: Linz PRO22SB/4, synchronous, brushless  
Poles: 4  
Fuel tank capacity (L): 130  
Consumption (L/h): 12.2 al 75% del carico  
Running time (h): 10.65 h al 75% del carico  
Length (mm): 2500  
Width (mm): 1000  
Height (mm): 1420  
Dry weight (Kg): 1390  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: AVR

