



# GREEN POWER GP22SH/YW-C SOUNDPROOF (MANUAL CONTROL UNIT)

**Product price:**

**6.054,00 € tax excluded**

**Product description:**

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

**Product features:**

Phase: Three phase

Maximum power three phase (KW): 16.8

Continuous power three phase (KW): 15.2

Maximum power three phase (KVA): 21

Continuous power three phase (KVA): 19

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: Yanmar 4TNV88, 4 stroke

Engine rpm (rpm): 1500

Speed governor: Mechanical



---

Starting system: Electric  
Engine capacity (cm³): 2190  
Number cylinders: 4  
Cylinders' position: In line  
Cooling: Water  
Alternator: LINZ E1S13M F/4(  
Poles: 4  
Fuel tank capacity (L): 70  
Consumption (L/h): 3.9 at 75% of the load  
Running time (h): 17.9 al 75% del carico  
Acoustic pressure: 67 dB(A)  
Length (mm): 1750  
Width (mm): 700  
Height (mm): 1125  
Dry weight (Kg): 515  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: Compound

