



PRAMAC LIFTER ELECTRIC PALLET TRUCK CX14 1150x525 EVO Li-Ion

Product price:

4,524.00 € tax excluded

Product description:

The CX electric pallet trucks are available in different versions equipped with MOSFET technology. They are suitable for carrying loads on smooth or paved surfaces. Its small size and turning radius make it the ideal tool to work with in confined spaces, such as lorries or narrow aisles.

Manoeuvrability

Thanks to the B1 width, which is equal to the fork gauge, and the L2 measurement of 360 mm, the CX12 electronic pallet truck is the ideal tool for the handling of pallets on lorries, in supermarket aisles and any application where space is limited. This machine is the best configuration in its category thanks to the frame width, in-service weight and turning radius, thus guaranteeing great manoeuvrability and compactness.

Steering wheel and controls

- Ergonomic tiller
- Luminous indicator for battery state control.
- Butterfly valves for traction control.
- Safety pushbutton with warning buzzer.
- Forks way up/down control positioned on both sides of the handle.
- Hour counter in the Plus and Gel versions.
- "Tortoise" pushbutton for slow motion, which allows for the carrying out of operations with the tiller in vertical position.

PLUS batteries



The Plus versions are equipped with semitraction batteries that guarantee greater autonomy and an operative life that allows for up to 5 times higher a number of charge life cycles. Thanks to the design of its guard, access to batteries is easy and rapid; this model also optimally combines size, power and low running cost also due to the integrated batteries and battery charger.

Stabilizers

Two stabilizing wheels enable movement even on more difficult surfaces thus guaranteeing maximum stability in any condition of use.

The images are purely indicative.

Product features:

Battery type: Li-Ion

Drive: Electric

Operator type: Pedestrian Load capacity (Kg): 1400

Load centre distance (mm): 600 Load axle to end forks (mm): 935

Wheel base (mm): 1195 Service weight (Kg): 255

Axle load, laden rear (Kg): 1047 Axle load, laden front (Kg): 609 Axle load, unladen front (Kg): 213 Axle load, unladen rear (Kg): 42 Tyres: front wheels: RUBBER Tyres: stabilizers wheels: POLY.C.

Tyres: rear wheels: POLY.C.

Diameter steering wheels (mm): 250 Width steering wheels (mm): 76 Diameter load rollers (mm): 82 Width load rollers (mm): 80

Diameter stabilizers wheels front (mm): 100 Width stabilizers wheels front (mm): 40

Quantity rear wheels: 2 Tread front (mm): 530 Tread rear (mm): 375 Lift height (mm): 115

Height of tiller in drive position max (mm): 1238



Height lowered (mm): 85 Overall lenght (mm): 1560

Lenght to face of forks (mm): 411

Overall width (mm): 720 Thickness fork (mm): 55 Width fork (mm): 150 Lenght fork (mm): 1150

Distance between fork arms (mm): 525

Ground clearance at centre of wheelbase (mm): 30

Aisle width (mm): 1810
Turning radius (mm): 1344
Travel speed laden (Km/h): 6
Travel speed unladen (Km/h): 6
Lifting speed laden (m/s): 0.03
Lifting speed unladen (m/s): 0.04
Lowering speed laden (m/s): 0.05
Lowering speed unladen (m/s): 0.04

Max gradeability laden (%): 5 Max gradeability unladen (%): 10

Service brake: Electric

Drive motor power (KW): 0.7 Lift motor power (KW): 1 Battery voltage (V): 24

Battery capacity min (Ah): 50 Battery capacity max (Ah): 50 Battery weight min (Kg): 14 Battery weight max (Kg): 14

Sound level at driver's ear: 59 dB(A)

