



GENSET MPM 400P ENGINE DRIVEN WELDER 16KVA 400A SINGLE/THREE PHASE AVR

Product price:

22.700,00 € tax excluded

Product description:

GENSET MPM 400P ENGINE DRIVEN WELDER 16KVA 400A SINGLE/THREE PHASE AVR

GENSET MPM 400P is a professional engine driven welder with electronic adjustment of welding parameters and Carbon Arc Gouging socket as standard.

The GENSET MPM 400P engine driven welder is an excellent solution for those looking for a versatile and reliable welding and power generation device. Manufactured by GenSet, this powerful and robust device offers high-level performance to meet both professional and domestic needs.

GENSET MPM 400P is equipped with a high-efficiency Perkins 404A-22G motor and can produce a maximum power of 16KVA, in addition thanks to the Electronic current regulation, it ensures a constant flow of energy to power welding equipment. This makes it ideal for large welding jobs or in places where grid electricity is not available.

The GENSET MPM 400P power welder is designed for ease of use and versatility. Equipped with an intuitive control panel, it makes it easy to adjust welding parameters and monitor current flow. It also offers a wide range of welding current options, allowing it to adapt to different welding needs.

This diesel engine welder is also characterized by its robustness and durability. Built with high-quality materials, it can withstand harsh working conditions and last for a long time. It is also equipped with safety protections, such as automatic shutdown devices in case of overheating or overload, ensuring safe and secure work.





The GENSET MPM 400P also offers a large fuel tank capacity, allowing long welding sessions without the need for continuous refueling. This makes the device suitable for long-duration work or situations where access to fuel may be limited.

WELDING CARBON ARC GOUGING

Carbon Arc Gouging welding, also known as carbon arc gouging, is a process of removing metal using an electric arc generated between a carbon electrode and the workpiece. This method is used to remove excess metal, rust, paint or other unwanted substances from the work surface.

Carbon Arc Gouging welding offers several advantages. It allows rapid removal of excess metal without damaging the underlying surface. It is particularly effective in removing hard materials such as stainless steel, cast iron or aluminum. In addition, the intensity of the arc can be adjusted to suit different metal removal needs.

TECHNICAL FEATURES GENSET MPM 400P

Phase Type: Single Phase / Three Phase

Maximum single-phase power: 5.5 KVA / 4.4 KW

Maximum three-phase power: 16 KVA / 12.8 KW

Voltage: 230 / 400 V

Frequency: 50 Hz

Engine: Perkins 404A-22G

Power Supply: Diesel

Emission standard: Stage Zero

Number of cylinders: 4

Displacement: 2216 cm³

Cooling: Water

Starter: Electric

Tank capacity: 70 l

Consumption at 75% load: 4 l/h

Autonomy at 75% load: 17.5 h

DC welding: Electronic regulation

Intermittency at 60%: 400 A - 36 V

Adjustment range: 30 A - 400 A

Trigger voltage: 70 V

Max. diameter. Electrode: 8 mm

Acoustic power: 67 dB(A) @ 7 m

Length: 1620 mm

Depth: 750 mm

Height: 1290 mm

Net Weight: 790 kg

Looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to GENSET or other specialized brands of engine driven welder.





Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 4.4

Maximum power single phase (KVA): 5.5

Maximum power three phase (KW): 12.8

Maximum power three phase (KVA): 16

Fuel: Diesel

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 2 x 230V/16A 2P+T CEE

Engine: Perkins 404A-22G

Emissions Regulations: Stage Zero

Engine rpm (rpm): 1500

Starting system: Electric

Engine capacity (cm³): 2216

Number cylinders: 4

Cooling: Water

Alternator: Asynchronous

Welding current (A): 350 A at 100% - 400 A at 60%

Open circuit voltage (V): 70

Fuel tank capacity (L): 70

Consumption (L/h): 4 to 75% of the load

Running time (h): 17.5 to 75% of the load

Acoustic power: 92 dB(A)

Acoustic pressure: 67 dB(A) at 7 m

Length (mm): 1620

Width (mm): 750

Height (mm): 1290

Dry weight (Kg): 790

Silenced: Yes

Super silenced: Yes

Voltage regulator: AVR

Engine manufacturer: Perkins

