



Shop name



GENSET MG 50 I-SY - SINGLE-PHASE/THREE-PHASE GENERATOR 44 KVA AVR

Product price:

18,329.00 € tax excluded

Product description:

GENSET MG 50 I-SY - SINGLE-PHASE- THREE-PHASE ELECTRIC GENERATOR 44 KVA AVR Stage 5

The three-phase 44 KVA diesel generator is the ideal solution for those who need a reliable and powerful energy source in professional or domestic contexts.

Main features GENSET MG 50 I-SY:

High power:

Maximum three-phase power: 44 KVA (35.2 kW)

Three-phase continuous power: 39.6 KVA (31.68 kW)

Single-phase maximum power: 14.6 KVA (11.68 kW)

Yanmar 4TNV98T (STAGE V) engine: 4-cylinder liquid-cooled diesel engine, reliable and high-performance, complying with STAGE V emission standards.

Electric start: Quick and easy starting with key.

Efficient consumption: Low fuel consumption (8.1 Lt/h) for optimum range.

Super silent: Soundproof design for quiet operation.

Robust construction: Compact and robust design for easy transport and storage.



Technical characteristics GENSET MG 50 I-SY

Maximum power Three-phase: 44 KVA
Maximum power Three-phase: 35.2 KW
Power continuous use Three-phase: 39.6 KVA
Power continuous use Three-phase: 31.68 KW
Maximum power Single-phase: 14.6 KVA
Maximum power Single-phase: 11.68 KW
Fuel: Diesel
Voltage: 230/400 V
Frequency: 50 Hz
Engine: Yanmar 4TNV98T (STAGE V)
Starting: Electric
Consumption: 8.1 Lt/h
Tank: 40 lt
Length: 1900 mm
Width: 910 mm
Height: 1100 mm
Weight: 735 Kg
Super silenced
AVR

If you are looking for a product like GENSET MG 50 I-SY with different characteristics click [HERE](#).

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 11.68
Maximum power single phase (KVA): 14.6
Maximum power three phase (KW): 35.2
Continuous power three phase (KW): 31.68
Maximum power three phase (KVA): 44
Continuous power three phase (KVA): 39.6
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 400V 63A CEE - 1 x 400V 32A CEE - 1 x 230V 32A CEE - 230V 16A CEE
Engine: Yanmar 4TNV98T, 4 stroke
Emissions Regulations: Stage 5



Engine rpm (rpm): 1500
Starting system: Electric
Engine capacity (cm³): 3319
Number cylinders: 4
Cooling: Water
Alternator: Synchronous
Protection degree: IP23
Motor insulation class: H
Fuel tank capacity (L): 40
Consumption (L/h): 8.1
Running time (h): 4.94
Acoustic power: 95 dB(A)
Acoustic pressure: 70 dB(A) at 7 m
Length (mm): 1900
Width (mm): 910
Height (mm): 1100
Dry weight (Kg): 735
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Yanmar