



MOSA CS 230 YSX CC / CV Multiprocess Welding Machine Stage 5 Engine

Product price:

4,740.00 € tax excluded

Product description:

MOSA CS 230 YSX CC / CV Multiprocess Welding Machine Stage 5 Engine

Mosa CS230YSX CC-CV Motor welder with electronic adjustment of the welding current in Chopper technology (high frequency 30 kHz), which allows a more stable arc welding and a higher metallographic quality.

Equipped with a Yanmar L 100 N engine and an asynchronous alternator, it can be used simultaneously as a welder and as a three-phase and single-phase generator.

The Mosa CS230YSX CC-CV Motosaldatrice is able to weld any type of electrode (basic, rutile, cellulosic) up to 4 mm and takes full advantage of the engine power thanks to a technique developed by MOSA, called " Power Optimizer ".

It is possible to select welding in CC or CV mode. In CC mode it is possible to choose between a characteristic with adjustable arc penetration (arc force), suitable for electrode welding and a strictly constant current characteristic, suitable for TIG (scratch striking) welding. CV (constant voltage) mode is suitable for WIRE WELDING (solid or cored).

Mosa CS230YSX CC-CV is a super-silenced engine driven welder with a compact fairing, specially designed to reduce noise emission. It is suitable for a wide range of applications.

TECHNICAL CHARACTERISTICS OF MOSA CS 230 YSX CC / CV

Fuel: Diesel

Phase type: Single-phase / Three-phase

Voltage: 48 V / 230 V / 400 V

Maximum single-phase power (kVA): 5

Maximum three-phase power (kVA): 10

Welding current (A): 350 A at 35% - 300 A at 60% - 250 A at 100%

Type of welding current: CC - CV

Type welding field: MMA / TIG / STICK / MIG (Optional)



Silenced: Silent 70 dB (A) @ 7 m
LENGTH (mm): 1230
WIDTH (mm): 690
HEIGHT (mm): 925
Dry weight (Kg): 345

discover all our [welders and engine driven welders by clicking here!](#)

The image is purely indicative.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KVA): 5
Maximum power three phase (KVA): 6
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1x400V 16A 3P+N+T CEE + 1x230V 16A 2P+T CEE + 1x230V 16A 2P+T SCHUKO
Engine: Yanmar L100 V (Stage 5)
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 435
Number cylinders: 2
Cooling: Air
Inyección : Direct
Alternator: Asynchronous three-phase, self-excited, self-regulated, brushless
Regulation current (A): 20 - 210
Welding current (A): 210 at 60% - 180 at 100%
Open circuit voltage (V): 65
Maximum diameter electrodes (mm): 4
Type of welding current: CC / CV
Type of welding: Multiprocess
Fuel tank capacity (L): 38
Consumption (L/h): 2.5
Running time (h): 15.2
Acoustic power: 94 dB(A)
Acoustic pressure: 69 dB(A) at 7 m
Length (mm): 1048
Width (mm): 648
Height (mm): 884



Shop name

Dry weight (Kg): 230

Silenced: Yes

Super silenced: Yes

Engine manufacturer: Yanmar



PrestaShop