



TF6 TORRE FARO 4x500W - COLONNA SUPER PRIMO 6 SFILI

Product price:

2.409,00 € tax excluded

Product description:

TF6 LIGHTING TOWER 4x500W SUPER PRIMO COLUMN 6 STAIRS

The Tower TF6 is equipped with a SUPER PRIMO Ø80 mm 6-stage telescopic pneumatic column in anodized aluminium, the lighting tower is equipped with 4 lamps of 500W.

The tower is complete with a hand pump for raising and locking manually on each extension to avoid the rotation of the same and to ensure the maximum extension of the column even in the absence of air inside.

The TF6 lighting tower stands out for its performance, compactness and solidity, with its 4X500W halogen lights, able to compete with much bulkier lighting towers equipped with a halogen system.

This range of lighting towers does not come with an integrated generator set, it is the ideal product for those who already have a power source or grid connection available.

The safety stop stops the descent at a safe height that avoids the risk of collision with the lights during the normal descent phase or in case of sudden breakage of the telescopic ropes or the automatic brake of the lifting winch.

The Light Tower is characterized by extremely compact dimensions that optimize and facilitate its positioning and transport on mobile means. The base, with 3 adjustable and removable anti-tip stabilizers, guarantees high wind stability.

TECHNICAL CHARACTERISTICS

Phase type: Single-phase

Voltage: 230 V

Projector type: Halogen Number of lamps: 4 x 500 W Maximum height: 6995 m





Minimum closed column height: 1625 mm Column material: Anodized aluminum Tripod structure diameter: 80 mm

Tripod leg length: 1100 mm

Looking for a light tower with different features? Here you can find the section dedicated to our selection of lighting towers of specialized brands

The images and technical data are not binding and may be subject to revisions by the supplier.

Product features:

Phase: Single phase Frequency (Hz): 50 Voltage (V): 230

Type of lamps: Halogen

Lamps: 4 x 500 W

Telescopic pole: Aluminum

Lifting System: Manual lifting system

Maximum height (m): 7 Height closed (mm): 1625 Transportability: Stationary

