



GENMAC Daily-GAS G5900HS NG GENERATOR 6,0KVA

Product price:

3,165.00 € tax excluded

Product description:

GENMAC Daily-GAS G5900HS NG THREE-PHASE GENERATOR 6,0KVA

The generator Genmac Daily-GAS G5900HS NG three-phase is equipped with a Honda engine powered by methane gas capable of delivering a power of 6,0KVA with capacitor voltage regulator (AVR optional).

Genmac silenced professional high quality natural generator with 6,0KVA power produced. Genmac is equipped with an oversized air-cooled Honda engine.

Genmac professional methane generators are highly reliable machines, built with quality components to be used in the professional field, where reliability is fundamental.

This feature is fundamental to guarantee a high reliability of the generator, reduces its effort and increases its life span by lowering the noise level.

All Honda engines are built using the best materials, the most innovative techniques and the most advanced methods for quality control.

Each engine is thoroughly tested in order to prove its perfect functioning before delivery.

In case of need, Honda's assistance service is always at your disposal.

The 6,0KVA generator is equipped with a capacitor voltage regulator, on request it can be supplied with the AVR regulator.

AVR Voltage Regulator

All Genmac series models are available with optional AVR voltage regulator. The AVR is a device that allows to keep the output more constant and less dependent on the load. Thanks to this card you have fewer drops or current peaks and this makes it safer to use the various devices connected, improving performance and durability.

The model equipped with AVR board is highly recommended, as it guarantees a significant



improvement in the stability of the output; this feature makes the generators particularly suitable for common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an increase in the life of your devices.

TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Daily-GAS G5900HS NG 6,0KVA

Voltage Regulator : Capacitor (AVR Optional)

Power Supply: Natural Gas

Firing: Electric

Phase Type: Single Phase / Three Phase

Single Phase Continuous Power: 1.8KVA / 1.4KW

Maximum Single Phase Power: 2KVA / 1. 6KW

Three-Phase Continuous Power: 5.4KVA / 4.3KW

Three-Phase Maximum Power: 6.0KVA / 4.8KW

Motor: Honda GX390

Socket Frame: 1 x 16A 230V / 1 x 32A 230V / 1 x 16A 400V

Voltage: 230 / 400 V

Frequency: 50 Hz

3000 turns per minute

Autonomy @ 75%: 1.76 h fixed turns

Acoustic pressure: 62 dB(A) @ 7 m

Length (mm): 1030

Width (mm): 620

Height (mm): 804

Dry weight (Kg): 183

If you are looking for another product then you can consult other terrestrial generators in [our catalog](#).

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 1.6

Continuous power single phase (KW): 1.4

Maximum power single phase (KVA): 2

Continuous power single phase (KVA): 1.8

Maximum power three phase (KW): 4.8

Continuous power three phase (KW): 4.3



Maximum power three phase (KVA): 6

Continuous power three phase (KVA): 5.4

Fuel: Natural Gas

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 16A 230V / 1 x 32A 230V / 1 x 16A 400V

Engine: Honda GX390

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Elettrico

Cooling: Air

Poles: 2

Consumption (L/h): 1.75 mc. @ 75%

Acoustic pressure: 62 dB(A) at 7 m

Length (mm): 1030

Width (mm): 620

Height (mm): 804

Dry weight (Kg): 183

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Honda

