



# VICTRON MultiPlus 48/1600/20-16 Charger- Inverter 48V 16A

**Product price:**

**700,00 € tax excluded**

## **Product description:**

VICTRON MultiPlus 48/1600/20-16 Charger-Inverter 48V 16A

The VICTRON MultiPlus 48/1600/20-16 is a powerful pure sine wave inverter and charger with adaptive charging technology and a high-speed AC transfer switch.

The VICTRON MultiPlus 48/1600/20-16 is an advanced 48V 16A charger-inverter, meticulously designed to tackle the challenges of advanced energy management. This device boasts a wide range of features that solidify its role as a crucial component within energy systems.

Its distinctive feature lies in its ability to operate in parallel with up to six MultiPlus units, thus harnessing enhanced output power. Further flexibility is offered by the option to configure three units for a three-phase output mode, providing versatility across various network configurations.

The Multi Control panel allows for setting a maximum current for the generator or grounding connection, preventing overloads from external sources. The innovative integration of PowerControl enables the VICTRON MultiPlus 48/1600/20-16 to seamlessly incorporate alternative energy sources. In times of high power demand, the device promptly compensates for energy deficits by tapping into the battery reserves. Conversely, during load reduction, excess energy recharges the battery, optimizing resource allocation.

Enhancing battery charging through a sophisticated adaptive four-stage charger, the VICTRON MultiPlus 48/1600/20-16 employs adaptive charging software to adapt to prevailing conditions. This progressive process smoothly transitions through three automatic stages, with a fourth stage catering to extended operational periods.

To ensure safety, the VICTRON MultiPlus 48/1600/20-16 is equipped with a programmable relay. This relay can be configured to function as an alarm, facilitating disconnection during pre-alarm or alarm scenarios, thereby providing an additional layer of security.



For convenient remote management, a three-pole connector streamlines operations, enabling remote activation, deactivation, and control of the charger. Once installed, the VICTRON MultiPlus 48/1600/20-16 is ready for use, while the option to adjust settings via DIP switches caters to the specific needs of each energy system. In summary, the VICTRON MultiPlus 48/1600/20-16 is a versatile, robust, and highly efficient component destined to drive advanced energy management in the future.

#### TECHNICAL FEATURES **VICTRON** MultiPlus 48/1600/20-16

PowerControl: Yes  
Parallel and Three-Phase Operation: Yes  
Transfer Switch: 16A

#### INVERTER

Input Voltage Range: 38 - 66 V  
Output Voltage: 230 VAC  $\pm$  2%  
Frequency: 50 Hz  $\pm$  0.1%  
Continuous Output Power at 25°C: 1600 VA  
Continuous Output Power at 25° / 40° / 65°: 1300 W / 1100 W / 800 W  
Peak Power 2800 W  
Maximum Efficiency 95%  
Zero-Load Power Consumption: 10 W  
Standby Power Consumption: 3 W

#### CHARGER

Input Voltage Range: 187-265 VAC  
Input Frequency: 45-65Hz  
"Absorption" Charge Voltage: 57.6 V  
"Float" Charge Voltage: 55.2 V  
Storage Mode Voltage: 52.8 V  
Service Battery Charge Current: 20 A  
Battery Temperature Sensor: Yes

Width: 265 mm  
Length: 120 mm  
Height: 470 mm  
Weight: 10.2 kg

Looking for a product with different technical specifications? Here, you can find the complete range of VICTRON chargers and inverters, as well as other specialized brands.

Images and technical data are not binding.





---

**Product features:**

Phase: Single phase

Frequency (Hz): 50 / 60

Voltage (V): 187-265

Protection degree: IP21

Output voltage (V): 230

Nominal current (A): 57.6

Charging voltage (V): 48

Length (mm): 470

Width (mm): 265

Height (mm): 120

Overload protectors: Yes

Input voltage (V): 48

Kind of wave: Pure Sinusoidal

Continuous power (W): 1300

Colour: Blue

Weight (Kg): 10.2

