



VICTRON MultiPlus-II 48/3000/35-32 Charger- Inverter 48V 32A

Product price:

880,00 € tax excluded

Product description:

VICTRON MultiPlus-II 48/3000/35-32 Charger-Inverter 48V 32A

VICTRON MultiPlus-II 48/3000/35-32 powerful pure sine wave inverter and adaptive charging technology charger with high-speed AC transfer switch.

The Charger-Inverter VICTRON MultiPlus-II 48/3000/35-32 is a versatile energy management solution that enhances the features of the MultiPlus, offering the additional option of an Energy Storage System (ESS). The VICTRON MultiPlus-II 48/3000/35-32 functions as an inverter/charger with extended PowerControl and PowerAssist capacities up to 32 A each, thanks to an external sensor option.

Designed for professional off-grid applications such as marine navigation, yachts, vehicles, and agriculture, the VICTRON MultiPlus-II 48/3000/35-32 features integrated anti-islanding functionality and an evolving list of certifications from various countries for ESS applications. System configurations are flexible and suitable for various needs, as described in the ESS design and configuration manual.

The PowerControl and PowerAssist functions enhance the capacity of the grid or generator. By setting a maximum input current from the grid or generator, the VICTRON MultiPlus-II 48/3000/35-32 intelligently manages loads and prioritizes battery charging to prevent overload. PowerAssist goes further by compensating for short-term high power demands using battery energy when the load exceeds supply and using excess energy to recharge the battery when the load decreases.

The integration of solar energy allows the Charger-Inverter VICTRON 48/3000/35-32 to operate autonomously by connecting to photovoltaic systems and other alternative sources. It is compatible with both solar charge controllers and grid-tied inverters.

With two AC outputs, the main output serves as a continuous power supply system, providing



instantaneous power during grid or generator interruptions. The second output is active only when AC input is available, adapting to loads that do not consume battery energy, such as water heaters.

VICTRON MultiPlus-II 48/3000/35-32 TECHNICAL SPECIFICATIONS

PowerControl and PowerAssist: Yes

Transfer switch: 32 A

Maximum AC input current: 32 A

INVERTER

DC input voltage range: 38 - 66 V

Output voltage: 230 VAC \pm 2%

Frequency: 50 Hz \pm 0.1% (1)

Continuous output power at 25 °C: 3000 VA

Continuous output power at 25° / 40 °C / 65°C: 2400 W / 2200 W / 1700 W

Maximum apparent input current: 3000 VA

Peak power: 5500 W

Maximum efficiency: 94%

Zero load power: 13 W

Power in AES stand-by mode: 9 W

CHARGER

Input voltage range: 187-265 VAC

Input frequency: 45-65 Hz

"Absorption" voltage: 57.6 V

"Float" voltage: 55.2 V

Storage mode voltage: 52.8 V

Maximum battery charge current: 35 A

Battery temperature sensor: Yes

Protection category: IP22

Width: 141 mm

Length: 268 mm

Height: 499 mm

Weight: 19 kg

Looking for a product with different technical specifications? Here you can find the complete range of VICTRON chargers and inverters, as well as other specialized brands.

Non-binding images and technical data.





Product features:

Phase: Single phase

Frequency (Hz): 50

Voltage (V): 187-265

Protection degree: IP21

Output voltage (V): 230

Nominal current (A): 57.6

Charging voltage (V): 48

Length (mm): 141

Width (mm): 268

Height (mm): 499

Overload protectors: Yes

Input voltage (V): 48

Kind of wave: Pure Sinusoidal

Continuous power (W):

Colour: Blue

Weight (Kg): 19

