



# CGM 25NG GAS METANO - APERTO CON CENTRALINA MANUALE

## Product description:

## Product features:

Phase: Single phase / Three phase

Maximum power three phase (KW): 26.4

Continuous power three phase (KW): 24

Maximum power three phase (KVA): 33

Continuous power three phase (KVA): 30

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 63A 5P CEE - 1 x 230V 16A 3P CEE

Engine: Lombardini LDW2204

Emissions Regulations: Stationary Use

Engine rpm (rpm): 3000

Speed governor: Electronic

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 2199

Number cylinders: 4

Cylinders' position: In line

Cooling: Water

Alternator: Linz, with brushes

Poles: 2

Bore x stroke (mm): 88 x 90.4

Fuel tank capacity (L): 50

Consumption (L/h): 8

Running time (h): 6.3

Acoustic pressure: 70 dB(A) at 7 m





Length (mm): 1600

Width (mm): 700

Height (mm): 1050

Dry weight (Kg): 500

Silenced: Yes

Super silenced: Yes

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Lombardini

