



TELAIR TG600MEF

Product price:

2,487.00 € tax excluded

Product description:

TELAIR TG600MEF CHARGER

TELAIR TG600MEF is a battery charger with more than double the charging capacity of a fuel cell or 100W solar panel Fully automatic.

The operation of the TELAIR TG600MEF charger is fully automatic, it is guaranteed by a combustion engine powered by the **LPG** on board, fuel with low environmental impact.

Thanks to a thick soundproof insulation, the TELAIR TG600MEF charger has an extremely low noise diffusion (only 51 dBA (7mt)) and almost imperceptible. The technical solutions adopted guarantee safe operation at all times, with negligible noise and vibrations.

System to manage **controlled** the **parallel** between the **motor battery** and the **service battery**.

The TELAIR TG600MEF charger starts when the battery is low (11.9V) and stops when it is full (14.5V). Useful when the engine battery is not completely efficient or when using high absorption electrical equipment

The TELAIR TG600MEF is charger with a simple and practical gas operation, just connect it to the gas bottle already present in the motorhome and it is ready to use

TELAIR TG600MEF is charger with a practical control panel that indicates high temperature and low oil level. In addition, the control panel is equipped with an indicator light that indicates all phases of ECOENERGY operation.

In addition, the panel is equipped with a button for forced manual start. It is used if you wish to switch on the ECOENERGY even if the battery voltage is above the minimum threshold level of 11.9 Volts. Once the 14.5 Volt voltage is reached, the ECOENERGY automatically switches the engine off and goes back into stand-by again.

TECHNICAL FEATURES OF TELAIR TG600MEF CHARGER CHARACTERISTICS



Automatic operation: Start 11.9V - Stop 14.5V
Operating temperature with propane gas: +50°C ÷ -25°C
Rated current: 25 A/h (480 A/24h)
Gas consumption/hour 290 g/h
Electrical power supply: Propane gas
Load voltage: 12V
Lubricating oil consumption: 1 lt/115 h
Noise at 7 mt LpA: 52 dBA
Weight 19 Kg
Length without brackets: 565 mm
Width without brackets: 380 mm
Height without brackets: 250 mm
Recommended batteries: 160 ÷ 300 Ah
Current supplied selectable: fixed
High mountain drive 2300 mt: NO
Connection cable with control unit 5 mt

Are you looking for a product with different characteristics? [HERE](#) you can find the entire TELAIR range and other specialist brands.

Images and technical data of TELAIR TG600MEF are not binding and may be modified by the manufacturer

Product features:

Fuel: Gas
Output voltage (V): 12
Nominal current (A): 25 A/h (600 A/24h)
Gas consumption (Kg/h): 0,29
Acoustic pressure: 52 dB(A) at 7 m
Length (mm): 565
Width (mm): 380
Height (mm): 250