



GENMAC QUEEN G100PS-E3 THREE-PHASE 100 KVA DIESEL - MOTOR PERKINS STAGE 3A

Product description:

GENMAC QUEEN G100PS-E3

The GENMAC QUEEN G100PS-E3 is a 100 KVA super-silenced single-phase/three-phase diesel generator with Stamford alternator and AVR voltage regulator.

Thanks to its diesel fuel supply, the GENMAC QUEEN G100PS-E3 can only consume 2.45 m³/h at full load and has a low environmental impact, making it one of the best in its class.

The long life and reliability of the GENMAC QUEEN G100PS-E3 is due to a special control procedure during the various stages of production.

The GENMAC QUEEN G100PS-E3 is suitable for applications in different contexts such as: hospitals, industries, shopping malls, hotels, airports, banks, universities, stadiums, offices, etc.

The Stage 3A engine allows the use of the generator set also for mobile use, for example for roadworks and rental services.

Control panel features

QT2A-4520

Self-standing tower with IP65 metal box
Circuit breaker
AMF controller DSE4520- Voltmeter, Frequency meter, Ammeter- Generator power (kW, kV Ar, kV A & pf) monitoring- Hour meter- Fuel level meter- Overload (kW & kV Ar) protection- Low oil pressure protection- High coolant temperature protection- Low fuel level protection- Battery charger alternator fault- Rpm protection
Emergency stop button
Audible alarm
Terminal board for ATS connection
Can Bus reading Port (if standard on the engine)
Battery charger
On/off switch

Images and technical data are not binding.



Product features:

Phase: Single phase / Three phase
Maximum power three phase (KW): 88
Continuous power three phase (KW): 80
Maximum power three phase (KVA): 110
Continuous power three phase (KVA): 100
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: PERKINS 1104D-E44TAG2, turbocharged
Emissions Regulations: Stage 3A
Engine rpm (rpm): 1500
Speed governor: Electronic
Engine capacity (cm³): 4400
Number cylinders: 4
Oil capacity (L): 8
Cooling: Water
Alternator: Stamford UCI274C, self-excited
Width (mm): 1056
Height (mm): 1900
Dry weight (Kg): 1684
AVR: Yes
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: Perkins