



LARIUS DALI K18957 AIRLESS DIAPHRAGM PUMP

Product price:

1.703,80 € tax excluded

Product description:

LARIUS DALI K18957 AIRLESS PUMP WITH MEMBRANE

LARIUS DALI K18957 is an electric pump for airless painting to be used in high pressure without the aid of air (hence the term AIRLESS) capable of delivering a maximum flow rate of 4 l/m.

LARIUS DALI K18957 is a high-pressure electric pump equipped with an exclusive electric piloting system that allows the safeguard of the motor and of the board, in case of lack of grounding, sudden changes of tension, overheating and inadequate electric extensions.

The LARIUS DALI K18957 pump is driven by an electric motor (burst) coupled to an eccentric shaft. The shaft goes to act on the hydraulic piston which, pumping oil from the hydraulic case, sends the suction diaphragm into fibrillation. The movement of the membrane creates a depression. The product is sucked in, pushed towards the outlet of the pump and sent through the hose to the guns

LARIUS DALI K18957 is able to apply in total efficiency in the aspiration and in the application of dense and viscous products, moreover thanks to the airless technology the drying times are considerably reduced, this allows the less contribution of diluting liquids to the product.

Thanks to LARIUS DALI K18957, the coating process will be faster and less costly; in fact, it makes it possible to cover the entire application zone in fewer passes.

All the components that characterize the pump LARIUS MIRÒ K21565 are of high quality and allow a very high resistance to wear and tear.

TECHNICAL FEATURES LARIUS DALI K18957

Max flow rate: 4 L/min

Motor power: 1.1 Kw



Max pressure: 250 bar
Power supply: 230 VAC
Frequency: 50 Hz
Available voltages: 115 VAC (60 Hz)
Available voltages: 400 VAC (50 Hz)
Guns: 1 AT 250 gun
Nozzle size: Up to 0. 025"
Minimum motor-generator power: 4.0 KW Single-phase
Length: 700 mm
Width: 500 mm
Height: 1000 mm
Weight: 38 Kg.

Looking for an electric pump with different features? Here you can find the whole range of LARIUS or other specialized brands.

The images are purely indicative

Product features:

Frequency (Hz): 50
Voltage (V): 230
Maximum output capacity (Lt/min): 4
Pressure (bars): 250 Max
Length (mm): 700
Width (mm): 500
Height (mm): 770
Dry weight (Kg): 38
Nozzle's largest diameter: 0.025"
Version: Trolley
Type of pumping group: Membrane

