



DIESEL Water cooled



# WFM KING KG160.2IV.tl.SS AUTOMATIC SILENCED GEN

## Product description:

WFM KING KG160.2IV.tl.SS AUTOMATIC SILENT ELECTRONIC GROUP

KING SIZE SERIES SOUNDPROOF VERSION

STANDARD GENERATOR SET EQUIPMENT

- Steel base
- Vibration dampers
- Integrated tank with liquid collection tank
- Industrial silencer for open version
- Battery
- AUTOMATIC SWITCHBOARD ACP 6120 AMF
- Engine with original tropicalized radiator
- Emergency stop button
- Galvanized steel soundproofing cabin with residential muffler

AUTOMATIC SWITCHBOARD ACP 6120 AMF

ELECTRICAL PANEL MOUNTED ON THE GENERATOR SET WITHOUT REMOTE CONTROL

Equipment: electronic control board, circuit breaker, battery charger, square key.

## Product features:

Phase: Three phase

Maximum power three phase (KW): 141





Continuous power three phase (KW): 128  
Maximum power three phase (KVA): 176  
Continuous power three phase (KVA): 160  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Terminal box  
Emissions Regulations: Stage 3A  
Engine rpm (rpm): 1500  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 6  
Number cylinders: 6  
Cylinders' position: In line  
Cooling: Water  
Inyección : Direct  
Alternator: Mecc Alte  
Poles: 4  
Three-phase power (KW): 128  
Three-phase power (KVA): 160  
Efficiency (%): 93.5  
Protection degree: IP21  
Bore x stroke (mm): 104 x 132  
Fuel tank capacity (L): 200  
Consumption (L/h): 24,8 @ 80%  
Running time (h): 8  
Length (mm): 3000  
Width (mm): 1130  
Height (mm): 1850  
Dry weight (Kg): 2350  
Silenced: Yes  
Brushes: No  
PMG: No  
Product type: Generator  
Type of alternator: Constant Speed  
Voltage regulator: AVR  
Engine manufacturer: FPT Iveco

