



GENSET MPM 500 Y 50/60 Hz - ENGINE DRIVEN WELDER 10 KVA

Product price:

11,799.00 € tax excluded

Product description:

MOTORWELDING MACHINE WITH ELECTRODE DC GENSET MPM 500 Y 50/60 Hz SINGLEPHASE 10 KVA

The motorwelder GENSET MPM 500 Y 50/60 Hz with 10 KVA singlephase diesel engine and electric start, suitable for electrode welding and gouging.

The GENSET MPM 500 Y motorwelder also has a low fuel consumption: only 3.5 Lt/h at 75% of the load.

The GENSET MPM 500 Y motorwelder, thanks to the high quality and efficiency of its components, is suitable for DC electrodes with a maximum diameter of 8 mm.

Main advantages of the GENSET MPM 500 Y 50/60 Hz motorwelding

CONTINUOUS CURRENT MOTORWELDING OF 500A WITH SINGLE-PHASE ALTERNATED
CURRENT GENERATOR DESEL ENGINE 1500/1800 RPM
70 L TANK

Technical characteristics of the GENSET MPM 500 Y 50/60 Hz motorwelding

Welding method: Electrode/Gouging

Automatic engine stop device with warning lights for:

- battery charge failure
- low fuel level
- low oil pressure
- high water temperature



1 CEE 32 A socket, 230V
1 CEE 32 A socket, 110V
1 CEE 16 A socket, 110V
Protection for power outlets
Battery 12V
Fuel level indicator
Single-phase voltmeter
Counter
50/60 Hz switch
Emergency stop button
Remote control socket
Forced Arc Adjustment potentiometer
Arc Gouging socket
Central lifting hook
Fork pass
Lwa noise level 95 (70 dB at 7 mt)
Dc welding 60 Hz
Intermittance at 60%: 450A - 38V
Intermittance at 100%: 400A - 36V
Electronic regulation (DC mode): 30A - 500A
Trigger voltage: 70V
Maximum electrode diameter: 8 mm
Ac generator 60 Hz
Type: asynchronous, self-excited and self-protected
Single-phase power (maximum): 10kVA - 240V / 5 kVA - 120 V
Power factor: $\cos \varphi$ 0.8
Ac generator 50 Hz
Type: asynchronous, self-excited and self-protected
Single-phase power (maximum): 10kVA - 230V / 5 kVA - 115 V
Power factor: $\cos \varphi$ 0.8
Diesel engine at 1500 or 1800 rpm Yanmar 4TNV88 - 4 cyl. - 2190 cm³
Maximum power: 24.1 HP (18 kWm) 1500 rpm - 29.4 HP (21.6 kWm) 1800 rpm
Boosting: electric (12Vdc)
Cooling system: water
Fuel consumption at 75% load: 3.5lt/h 1500 rpm - 4.7lt/h 1800 rpm
Isolation class: H
Ambient temperature: 40 °C (*)
Reference altitude: 1000 m (*)
Protection class: IP 23
Fuel tank capacity: 70 lt
Dimensions (L x W x H): 1855 x 737 x 1119 mm
Dry weight: 895 kg

Options to specify when ordering



On-board polarity inverter
Spark arrester muffler
Differential switch (ELCB) for single-phase 240/230 V output
Differential switch (ELCB) for single-phase 120/115 V output
MIG welding
TIG welding
Automatic stop for low coolant level
GRT2W: trolley with 2 pneumatic wheels and drawbar for slow towing
GRT4W: trolley with 4 pneumatic wheels and drawbar for slow towing
Remote control unit 20 mt cable
Welding cables Ø 50 mm² (20+15 mt) with accessories
Polarity reverser module

Discover our wide range of motorwelding [click here!](#)

Images and technical data not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 8
Maximum power single phase (KVA): 10
Fuel: Diesel
Frequency (Hz): 50 / 60
Voltage (V): 115 / 230
Sockets configuration: 1 x 230V 32A CEE - 1 x 110V 32A CEE - 1 x 110V 16A CEE
Engine: Yanmar 4TNV88, 4 stroke
Engine rpm (rpm): 1500 / 1800
Starting system: Elettrico
Engine capacity (cm³): 2190
Number cylinders: 4
Cooling: Water
Alternator: Asincrono
Protection degree: IP23
Motor insulation class: H
Regulation current (A): 30 - 500
Open circuit voltage (V): 70
Maximum diameter electrodes (mm): 8
Intermittence: 450 A al 60% / 400 A al 100%
Fuel tank capacity (L): 70
Consumption (L/h): 3.5
Running time (h): 20
Acoustic power: 95 dB(A)



Shop name

Acoustic pressure: 70 dB(A) at 7 m
Length (mm): 1855
Width (mm): 737
Height (mm): 1119
Dry weight (Kg): 895
Silenced: Yes
Super silenced: Yes
Product type: Engine driven welder
Voltage regulator: No
Engine manufacturer: Yanmar



PrestaShop