



GENERATOR SET GP33S-P-N-A SOUNDPROOF

Product price:

7,977.00 € tax excluded

Product description:

The GP33S-P-N-A 1500 rpm generator sets are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Sturdy electrowelded steel frames with built-in variable capacity tank, engines and alternators supplied by the world's leading manufacturers in the sector and state-of-the-art control units are the elements to guarantee excellent quality generators.

The casings are made of steel, which allows their use also in tropical environments. The casings of the GP33S-P-N-A guarantee maximum accessibility for maintenance and cleaning operations.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 26.4 Continuous power three phase (KW): 24 Maximum power three phase (KVA): 33 Continuous power three phase (KVA): 30

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: Terminal box

Engine: PERKINS 1103A-33G, 4 stroke naturally aspirated

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500 Speed governor: Mechanical Starting system: Electric Engine capacity (cm³): 3300



Number cylinders: 3

Cylinders' position: In line

Cooling: Water

Alternator: Mecc Alte

Poles: 4

Fuel tank capacity (L): 100

Consumption (L/h): 5.4 at 75% of the load Running time (h): 18.5 at 75% of the load

Acoustic pressure: 61 dB(A) at 7 m

Length (mm): 2100 Width (mm): 900 Height (mm): 1150 Dry weight (Kg): 940

Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Perkins

Precision of voltage regulation: ± 1%