



KOHLER 55EFOZDJ Three-phase 69 kVA 50 Hz Marine Generator Set

Product price:

78,700.00 € tax excluded

Product description:

Super-silenced KOHLER 55EFOZDJ Marine Generator 69 KVA AVR

Kohler 55EFOZDJ three-phase 69 KVA and single-phase 50 KVA marine generator with 1500 rpm motor. The KOHLER 55EFOZDJ is built with a soundproof enclosure that makes it **supersilenced**. The KOHLER 55EFOZDJ is built with a 4-cylinder diesel-powered John Deere engine. The alternator of the KOHLER 55EFOZDJ marine generator is brushless with **AVR** voltage regulator and water-cooled. With its small size, the 55EFOZDJ marine generator is perfect for installation on boats of various sizes.

Technical data:

Phase type: Three-phase

Three-phase continuous power: 52 KW

Three-phase continuous power: 69 KVA

Permanent magnet brushless alternator

Heat exchanger/ Cooled keel

Fuel: Diesel

Frequency: 50 Hz

Voltage: 110/190 V, 110/220 V, 120/208 V, 115/230 V, 220/380 V, 230/400 V, 240/416 V

Motor: John Deere

Electrical system 24v c. c.

Engine speed: 1500 rpm

Length: 1690 mm

Width: 767 mm

Height: 1015 mm

Dry weight: 1098 Kg

Features of the KOHLER 55EFOZDJ

- The engine is Environmental Protection Agency (EPA) Tier III compliant (60 Hz model only)



-
- The unique Fast-Responser X excitation system provides excellent voltage response and short-circuit capability using a rare earth permanent magnet excited alternator
 - The rotating field brushless alternator has wide range reconnectability
 - Remote control connector
 - Class H insulation
 - Connectable voltage
 - Single or three phase reconnectable alternator
 - Voltage regulation of $\pm 0, 5\%$.
 - Frequency adjustment of 0.5% .
 - Cooled heat exchanger configuration includes an exhaust curve
 - Cooled keel configuration includes a dry exhaust curve

Engine features of the KOHLER 55EFOZDJ

- One-sided serviceability of fuel system, lubrication system and air filter
- Low oil pressure cutout
- High water temperature cutout
- Coolant cutout leakage
- Overcrank cutout
- Belt guard
- Optional digital gauge
- Disposable oil filter
- Extended oil drain
- PTO options: 12- or 24-volt electric clutch

Kohler 55EFOZDJ alternator features

- Compliant with NEMA MG1, IEEE and ANSI standards for temperature rise and engine starting.
- Able to withstand a line-to-neutral short-circuit current of up to 300% of rated current for up to 2 seconds. Able to withstand sustained short circuit current up to 300% of rated current for up to 10 seconds for 3 phase connections. (Short-circuit performance IEC 60092-301).
- Sustained short-circuit current allowing downstream circuit breakers to trip without collapsing the alternator field.
- Self-ventilated and watertight construction.
- Vacuum-impregnated windings with epoxy paint for reliability and long life.
- Superior voltage waveform from a two-thirds pitch stator and inclined rotor.

If you are looking for marine generators like the KOHLER 55EFOZDJ but with different features you can view the entire catalog of [marine generators](#).

Pictures and technical data are not binding.

Product features:



Phase: Single phase / Three phase
Continuous power single phase (KW): 50
Continuous power single phase (KVA): 50
Continuous power three phase (KW): 55
Continuous power three phase (KVA): 69
Fuel: Diesel
Frequency (Hz): 50
Engine: John Deere
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Speed governor: Electronic
Engine capacity (cm³): 4500
Number cylinders: 4
Cylinders' position: In line
Oil capacity (L): 15
Cooling: Water
Inyección : Direct
Alternator: Permanent magnets
Poles: 4
Bore x stroke (mm): 106 x 127
Compression ratio: 16 : 1
Motor insulation class: H
Consumption (L/h): 8.74 @ 75%
Length (mm):
Width (mm): 767
Height (mm): 1015
Dry weight (Kg): 1095
Silenced: Yes
Super silenced: Yes
Brushes: No
PMG: Yes
Input voltage (V): 24
Type of combustion: Direct
Product type: Generator
Type of alternator: Constant Speed
Voltage regulator: AVR
Engine manufacturer: John Deere

