

## CGM D11000T GENERATORS THREE PHASE 11KVA

Product price:

## 4.845,00 € tax excluded

## **Product description:**

Ø.

CGM D11000T THREE-PHASE GENERATOR 11KVA

Generator CGM D11000T with KOHLER KD425 STAGE V Diesel engine, capable of delivering a power of 11KVA, compact and easy to use, mounted on a fixed base with rubber vibration dampers.

The CGM D11000T Generator consists of a Made in Italy alternator from Linz or NSM, selfexcited without brushes and with **AVR** voltage regulator. The CGM D11000T generator is equipped with electric start with 12V battery and with a low fuel consumption, in fact it consumes only 2,8 liters/hour at 75% of the load.

This generator is perfect for outdoor use such as hobby use. Also available with a panel for automatic starting with ATS.

The CGM D11000T generator is part of the CLASSIC DIESEL series and are characterized by lower consumption and a longer life expectancy than the gasoline-powered range. The 3000 rpm generator is suitable for emergency use only. It is not recommended to use it for more than 6 hours continuously and for more than 500 hours per year.

Technical Features of the CGM D11000T Generator

Type of phase: Singlephase / Threephase Maximum singlephase power: 4 KVA / 3.2 KW Continuous singlephase power: 3.6 KVA / 3 KW Maximum threephase power: 12.1 KVA / 9.7 KW Continuous threephase power: 11 KVA / 8.8 KW Fuel: Diesel Voltage: 230/400 V Frequency: 50 Hz Power factor cos: 0.8

PrestaShop

R)

Socket configuration: 1 CEE 16A 3P 230V socket and 1 CEE 16A 5P 400V socket Switch, thermal protection, voltmeter, hour counter Motor: KOHLER KD425 Emissions Regulations : STAGE V Displacement cc: 851 Engine revolutions: 3000 rpm Number and arrangement of cylinders: 2 Cooling system: Air Starting: Electric Alternator: Linz or NSM Poles: 2 Voltage regulator system: AVR Consumption: 2.8 Lt / h at 75% of the load Tank capacity: 4 Lt Autonomy: 1.4 h at 75% of the load Length: 910 mm Width: 580 mm Height: 640 mm Weight: 170 Kg

Are you looking for a generator with different technical characteristics? Here you can find the full range of CGM generators or other specialized brands.

The pictures and technical data are not binding and may be subject to revisions by the manufacturer.

## **Product features:**

Ø.

Phase: Single phase / Three phase Maximum power single phase (KW): 3.2 Continuous power single phase (KVA): 3 Maximum power single phase (KVA): 4 Continuous power single phase (KVA): 3.6 Maximum power three phase (KW): 9.7 Continuous power three phase (KW): 8.8 Maximum power three phase (KVA): 12 Continuous power three phase (KVA): 12 Continuous power three phase (KVA): 11 Fuel: Diesel Frequency (Hz): 50 Voltage (V): 230 / 400 Sockets configuration: 1 CEE 16A 3P 230V + 1 CEE 16A 5P 400V Engine: Kohler KD 425/2 Emissions Regulations: Stage 5

PrestaShop

R

Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm<sup>3</sup>): 851 Number cylinders: 2 Cooling: Air Alternator: Linz or NSM Poles: 2 Fuel tank capacity (L): 4 Consumption (L/h): 2.8 at 75% of the load Running time (h): 1.4 at 75% of the load Length (mm): 910 Width (mm): 580 Height (mm): 640 Dry weight (Kg): 170 Voltage regulator: AVR

R