



CGM DS6000-RE SINGLE-PHASE GENERATOR 6KVA

Product price:

4,562.50 € tax excluded

Product description:

CGM DS6000-RE single-phase 6 KVA super-silenced generator

CGM DS6000-RE single-phase 6 KVA generator set with Kohler engine powered by STAGE V diesel at 3000 rpm, compact and easy to use, equipped with enclosure that lowers noise emissions and makes it **supersilenced**.

The CGM DS6000-RE generator set is composed of a Made in Italy alternator from Linz or NSM, self-excited without brushes and with voltage regulator **AVR**. The CGM DS6000-RE generator set is equipped with electric start with 12V battery and with a low fuel consumption, in fact it consumes only 1,5 liters/hour at 75% of the load. This CGM DS6000-RE genset is perfect for outdoor use.

The CGM DS6000-RE is part of the QUIET series and are characterized by lower fuel consumption and a longer life expectancy than the gasoline powered range and equipped with a soundproof cabin suitable for installation and outdoor use, and increased fuel tank. The CGM DS6000-RE generator set at 3000 rpm is suitable for emergency use only. It is not recommended for use for more than 6 hours continuously and for more than 500 hours per year.

Technical characteristics of the CGM DS6000-RE:

Phase type: Single phase
Maximum power: 5.9 KW
Continuous power: 5.4 KW
Maximum power: 6.6 KVA
Continuous power: 6 KVA
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Motor: KOHLER KD15-440
Engine speed: 3000 rpm



Starting: Electric
Voltage regulator system: AVR
Consumption: 1.5 Lt/h at 75% of the load
Tank capacity: 30 Lt
Autonomy: 20 h at 75% load
Length: 1100 mm
Width: 650 mm
Height: 900 mm
Weight: 200 Kg
Supersilenced

Discover the full range reserved for [generators](#) of [CGM](#) or other top brands by browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 5.9
Continuous power single phase (KW): 5.4
Maximum power single phase (KVA): 6.6
Continuous power single phase (KVA): 6
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 16A 3P - 1 x 230V 32A 3P - 1 x 230V SCHUKO
Engine: Kohler KD 15-440
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 442
Number cylinders: 1
Alternator: Made in Italy
Poles: 2
Voltage regulator: AVR