



VILLAGE MARINE WATERMAKER LTM-800 230-460V 50-60Hz

Product description:

Village Marine Watermaker LTM-800 230-460V 50-60Hz

Village Marine LTM-800 three phase desalinator with 230-460 V power supply and 50-60 Hz frequency. The Village Marine LTM-800 desalinator has a capacity of 125 litres/hour.

The LTM-800 Village Marine Desalinator offer high quality Parker Village Marine engineered components with simple manual operation. Driven by AC motors, the modular configuration is ready to mount modules for flexible installation options. Integrated into each LTM unit is a control manifold, which includes a regulator and a bypass valve.

Some specifications of the LTM-800 Desalinator

- Powder coated mounting brackets included
- 5 micron of cleanable prefilter
- The control manifold pressure regulator ensures constant pressure and prevents over- or under-pressurization of the unit. Adjustable to allow operation in brackish or fresh water
- High-quality spiral wound TFC reverse osmosis membranes with spiral wound
- Magnetic drive thrust pump
- Stainless steel pressure gauges filled with glycerine
- High pressure piston pump with 316 stainless steel head
- Acrylic flowmeter for production monitoring

Technical characteristics:

Phase type: Three-phase

Power supply: 230-460 VDC

Frequency: 50-60 Hz

Flow rate: 125 Lt/h

Weight: 45 Kg

If you are looking for another desalinator similar to the Village Marine LTM-800 then you can browse our entire catalogue dedicated to marine desalinators.

Images and technical data are not binding.

Product features:

Phase: Three phase

Frequency (Hz): 50 / 60

Feed Type: 230-460 V

Capacity (Lt/h): 125

Weight (Kg): 45