



IDROMAR WATERMAKER MC12S

Product price:

23.000,00 € tax excluded

Product description:

IDROMAR WATERMAKER MC12S

Watermaker Idromar MC12S, part of the MINI COMPACT series, is an excellent Watermaker with an hourly production of fresh water at 25°C equal to 500 litres/hour and a daily production at 25°C equal to 12000 litres/day.

The 4 models of the Senior series, such as the Watermaker Idromar MC12S, while maintaining small size and low power consumption, are the answer and the immediate solution to a demand for machines that are increasingly reliable, simple and capable of working at high rates.

The Watermaker of the Senior series, such as the Idromar MC12S, as well as the Junior series, can always be dismantled into several parts for easy maintenance and are completely adaptable to the available space. They are equipped with a complete and readable instrumentation and at the same time are extremely functional with alarm devices that intervene even in case of false operation.

The Watermaker Idromar MC12S provides a practical and reliable source of fresh water to boaters with high supply requirements. The Idromar MC12S Watermaker offers you absolute water independence for various diversions such as extended voyages, ocean crossings or fishing.

The Idromar MC12S Watermaker systems are small and efficient able to fit into the tightest of spaces due to their complete decomposability.

Technical characteristics of the Watermaker Idromar MC12S:

Hourly production at 25°C: 500 Lt/h

Daily production at 25°C: 12000 Lt/day

Produced water salinity: 300/400 PPM

Power consumption: 6 KW

Length: 1070 mm



Width: 650 mm
Height: 800 mm
Weight: 185 Kg

Hydraulic connections

Sea suction: 1"
Caskets suction: 1"
Exhaust: 1"
Production: 1/2"

If you are looking for another watermaker similar to the Idromar MC12S then we recommend you browse our entire catalog dedicated to the nautical watermakers.

Images and technical data are not binding.

Product features:

Power (W): 6000
Length (mm): 1070
Width (mm): 650
Height (mm): 800
Feed Type: 230 V
Production for hour at 25°C (Lt/h): 500
Daily production at 25°C (Lt/day): 12000
Salinity of water produced (PPM): 300/400
Capacity (Lt/h): 500
Remote panel: Digital
Weight (Kg): 185

