



CGM C13000T

Product price:

2,520.00 € tax excluded

Product description:

CGM C13000T Three-phase generating set 12KVA

CGM C13000T Three-phase generator 12KVA with Briggs & Stratton engine powered by STAGE V gasoline at 3000 rpm, compact and easy to use, mounted on a fixed base with rubber vibration dampers.

The CGM C13000T generator is composed of a Made in Italy alternator from Linz or NSM, self-excited with brushes and with AVR voltage regulator.

The CGM C13000T generator is equipped with manual recoil start and low fuel consumption, in fact it consumes only 4.3 liters/hour at 75% of the load for an autonomy of up to 3 hours of operation.

This CGM C13000T is perfect for outdoor use such as hobby use. It is also available in a version with electric key start and with a panel for automatic start with ATS.

The CGM C13000T is part of the CLASSIC series and is easily adaptable to a variety of uses such as homes, mobile facilities, campgrounds, hobbies, construction sites, etc. The CGM C13000T generator set at 3000 rpm is suitable for emergency use only. It is not recommended to be used for more than 6 hours continuously and for more than 500 hours per year.

Technical specifications of CGM C13000T:

Type of phase: Singlephase / Threephase

Maximum singlephase power: 4.4 KVA / 3.5KW

Continuous singlephase power: 4 KVA / 3.2 KW

Maximum threephase power: 13.2 KVA / 10.5 KW

Continuous threephase power: 12 KVA / 9.6 KW

Fuel: Petrol

Voltage: 230/400 V

Frequency: 50 Hz



Motor: BRIGGS & STRATTON 18HP

Engine revolutions: 3000 rpm

Starting: Manual

Voltage regulator system: AVR

Consumption: 4.3 Lt / h at 75% of the load

Capacity tank: 8.5 Lt

Autonomy: 2 h at 75% of the load

Length: 910 mm

Width: 580 mm

Height: 640 mm

Weight: 111 Kg

Discover the full range reserved for [generator](#) of CGM or other top brands by browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 3.5

Continuous power single phase (KW): 3.2

Maximum power single phase (KVA):

Continuous power single phase (KVA): 4

Maximum power three phase (KW):

Continuous power three phase (KW): 9.6

Maximum power three phase (KVA): 13.2

Continuous power three phase (KVA): 12

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration:

Engine: Briggs&Stratton

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000



Starting system: Manuale

Engine capacity (cm³): 570

Number cylinders: 2

Alternator: Made in Italy

Poles: 2

Fuel tank capacity (L):

Consumption (L/h): 4.3

Running time (h): 2

Length (mm): 910

Width (mm): 580

Height (mm): 640

Dry weight (Kg): 111

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Briggs&Stratton

