



## CGM D4000T

**Product price:**

**2.850,00 € tax excluded**

### **Product description:**

CGM D4000T three-phase generator 4KVA

CGM D4000T three-phase generator 4KVA with a Kohler engine powered by STAGE V diesel at 3000 rpm, compact and easy to use, mounted on a fixed base with vibration dampers.

The CGM D4000T generator set is composed of a Made in Italy alternator by Linz or NSM, self-excited with brushes and with AVR voltage regulator. The CGM D4000T generator set is equipped with electric start with 12 V battery and with a low fuel consumption, in fact it consumes only 1 liter/hour at 75% of the load.

This CGM D4000T is perfect for outdoor use such as hobby use.

The CGM D4000T generator set is part of the CLASSIC DIESEL series and are characterized by lower consumption and a longer life expectancy than the gasoline powered range. The CGM D4000T at 3000 rpm is suitable for emergency use only. It is not recommended for use for more than 6 hours continuously and for more than 500 hours per year.

### **Technical characteristics of CGM D4000T:**

Type of phase: Singlephase / Threephase

Maximum singlephase power: 1.5 KVA / 1.2 KW

Continuous singlephase power: 1.3 KVA / 1 KW

Maximum threephase power: 4.4 KVA / 3.5 KW

Continuous threephase power: 4 KVA / 3.2 KW

Fuel: Diesel

Voltage: 230/400 V

Frequency: 50 Hz

Motor: KOHLER KD15-350

Engine rpm: 3000 rpm



Starting: Electric  
Voltage regulator system: AVR  
Consumption: 1 Lt / h at 75% of the load  
Capacity tank: 4.3 Lt  
Autonomy: 4.3 h at 75% of the load  
Length: 780 mm  
Width: 510 mm  
Height: 500 mm  
Weight: 80 Kg

Discover the full range reserved for generators of CGM or other top brands by browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

#### **Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 1.2  
Continuous power single phase (KW): 1  
Maximum power single phase (KVA): 1.5  
Continuous power single phase (KVA): 1.3  
Maximum power three phase (KW): 3.5  
Continuous power three phase (KW): 3.2  
Maximum power three phase (KVA): 4.4  
Continuous power three phase (KVA): 4  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 400V 16A 5P CEE - 1 x 230V 16A 3P CEE  
Engine: Kohler KD 15-350  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 349  
Number cylinders: 1  
Alternator: Made in Italy  
Poles: 2  
Fuel tank capacity (L): 4.3  
Consumption (L/h): 1  
Running time (h): 4.3





---

Length (mm): 780  
Width (mm): 510  
Height (mm): 500  
Dry weight (Kg): 80  
Silenced: No  
Super silenced: No  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Kohler

