

# CGM DS4000T

Product price:

# 4.400,00 € tax excluded

### **Product description:**

Ø.

Three-phase CGM DS4000T generator set 4 KVA Supersilenced

CGM DS4000T three-phase 4 KVA generator set with a Kohler engine powered by STAGE V diesel at 3000 rpm, compact and easy to use, equipped with enclosure that lowers noise emissions and makes it **super-silenced**.

The CGM DS4000T is composed of a Made in Italy alternator from Linz or NSM, self-excited with brushes and with AVR voltage regulator. The CGM DS4000T generator set is equipped with electric start with 12 V battery and with a low fuel consumption, in fact it consumes only 1 liter/hour at 75% of the load. This CGM DS4000T is perfect for outdoor use.

The CGM DS4000T is part of the QUIET series and are characterized by lower fuel consumption and a longer life expectancy than the gasoline-powered range and equipped with soundproof cabin suitable for installation and outdoor use, and increased fuel tank. The CGM DS4000Tgenerator set at 3000 rpm is suitable for emergency use only. It is not recommended to be used for more than 6 hours continuously and for more than 500 hours per year.

### Technical features of CGM DS4000T:

Phase type: Three phase Maximum power: 3.5 KW Continuous power: 3.2 KW Maximum power: 4.4 KVA Continuous power: 4 KVA Fuel: Diesel Voltage: 400 V Frequency: 50 Hz Motor: KOHLER KD15-350 Engine speed: 3000 rpm Starter: Electric

(RI)

Voltage regulator system: AVR Consumption: 1 Lt/h at 75% of the load Tank capacity: 30 Lt Autonomy: 30 h at 75% load Length: 1100 mm Width: 650 mm Height: 900 mm Weight: 160 Kg Supersilenced

Discover the full range reserved for generator of CGM or other top brands browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding.

### **Product features:**

Ø.

Phase: Three phase Maximum power three phase (KW): 3.5 Continuous power three phase (KW): 3.2 Maximum power three phase (KVA): 4.4 Continuous power three phase (KVA): 4 Fuel: Diesel Frequency (Hz): 50 Voltage (V): 400 Sockets configuration: 1 x 400V 16A 5P CEE - 1 x 230V 16A 3P CEE - 1 x 230V SCHUKO Engine: Kohler KD 15-350 **Emissions Regulations: Stage 5** Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm<sup>3</sup>): 349 Number cylinders: 1 Alternator: Made in Italy Poles: 2 Fuel tank capacity (L): 30 Consumption (L/h): 1 Running time (h): 30 Length (mm): 1100 Width (mm): 650 Height (mm): 900 Dry weight (Kg): 160 Silenced: Yes Super silenced: Yes

Product type: Generator ATS Switch device : Optional Voltage regulator: AVR Engine manufacturer: Kohler

R