



CGM PR7000E

Product price:

2,280.00 € tax excluded

Product description:

CGM PR7000E Single-phase 7 KVA AVR generator

CGM PR7000E is a 7 KVA single-phase generator set with a Honda engine powered by STAGE V petrol at 3000 rpm, compact and easy to use, mounted on a fixed base with vibration dampers. The CGM PR7000E current generator consists of a Made in Italy alternator from Linz or NSM, self-excited with brushes and AVR voltage regulator.

The CGM PR7000E is equipped with an electric starter with 12 V battery and low fuel consumption, in fact it consumes only 2 litres/hour at 75% of the load. This CGM PR7000E power generator is perfect for outdoor use such as hobby use.

The CGM PR7000E is part of the new PROFESSIONAL range which is the evolution of the DELUXE petrol range. This power generator, like all those in the PROFESSIONAL series, is robust and easy to handle, designed specifically for professionals and singers. These generators are equipped with a dedicated electrical panel with differential protection and oversized rain cover.

The CGM PR7000E generator set at 3000 rpm is suitable for emergency use only. It is not recommended to use it for more than 6 hours continuously and for more than 500 hours per year.

The electric panel of the CGM PR7000E is composed of:

- N.1 230V Schuko + N.1 230V 16A 3P CEE + N.1 230V 32A 3P CEE
- 12VDC socket
- Multimeter and hour counter
- Thermal-magnetic and differential switch

Technical characteristics of the CGM PR7000E:

Phase type: Single-phase

Maximum single-phase power: 6.9 KW Single-phase continuous power: 6.3 KW



Maximum single-phase power: 7.7 KVA Single-phase continuous power: 7 KVA

Fuel: Petrol Voltage: 230 V Frequency: 50 Hz Motor: HONDA GX390 Engine revs: 3000 rpm

Start-up: Electric Tank capacity: 15 Lt

Consumption: 2 Lt/h at 75% of load Autonomy: 7.5 h at 75% of the load

Length: 825 mm Width: 550 mm Height: 530 mm Weight: 90 Kg

AVR

Discover the entire range reserved for CGM generators or other top brands by browsing our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 6.9 Continuous power single phase (KW): 6.3 Maximum power single phase (KVA): 7.7 Continuous power single phase (KVA): 7

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 1 x 230V 16A 3P CEE - 1 x 230V 32A 3P CEE - 1 x 230V SCHUKO

Engine: Honda GX390

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Starting system: Elettrico Engine capacity (cm³): 389

Number cylinders: 1 Alternator: Made in Italy

Poles: 2

Fuel tank capacity (L): 15 Consumption (L/h): 2



Running time (h): 7.5 Length (mm): 825 Width (mm): 550 Height (mm): 530 Dry weight (Kg): 90

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Honda

