

HELVI SPEEDY 250

Product price:

169,65 € tax excluded

Product description:

Ì

HELVI SPEEDY250 Battery charger

HELVI SPEEDY250 is a battery charger with starter, portable with charge current selector, ammeter, thermostatic protection against long starts, internal fuse against short circuits and polarity reversal.

The HELVI SPEEDY250 battery charger is perfect for charging batteries with 12 V or 24 V voltage and 18 A current.

The HELVI SPEEDY250 battery charger can charge batteries for various types of vehicles such as cars, vans, boats and tractors. The main applications of the HELVI SPEEDY250 battery charger are in the automotive, domestic and agricultural sectors.

HELVI SPEEDY250 is a single-phase battery charger with 230 V power supply and 50/60 Hz frequency. The HELVI SPEEDY250 battery charger has a rated power of 650 W for a maximum current of 27 A.

The nominal charging capacity of the HELVI SPEEDY250 charger is 270 Ah and has 2 charging positions (min-max) plus Boost.

HELVI SPEEDY250 is very compact and very light thanks to its weight of about 10 Kg.

Technical characteristics of the HELVI SPEEDY250 battery charger:

Phase type: Single-phase Voltage: 230 V Frequency: 50/60 Hz Power: 650 W Battery voltage: 12/24 V Maximum current: 27 A Charging current: 18 A Maximum surge current: 220 Acc Charging capacity: 270 Ah 15h Charging positions: 2 + Boost Length: 235 mm

PrestaShop

R)

Width: 220 mm Height: 335 mm Weight: 10.7 Kg

Ø.

If you are looking for another product similar to the HELVI SPEEDY250 portable charger, then we recommend that you take a look at the entire range dedicated to battery chargers.

Images and technical data are not binding.

Product features:

Phase: Single phase Frequency (Hz): 50 / 60 Voltage (V): 230 Power (W): 650 Adjustment positions: 2 + Boost Nominal current (A): 18 Charge capacity (Ah): 270 Battery voltage (V): 12 / 24 Charging voltage (V): 12 / 24 Current max (A): 27 Length (mm): 235 Width (mm): 235 Width (mm): 335 Product type: Battery Charger Weight (Kg): 10.7