



HELVI AUTOSTAR 500

Product price:

353.70 € tax excluded

Product description:

HELVI AUTOSTAR500 Battery charger

HELVI AUTOSTAR500 is a battery charger with portable starter equipped with selector and ammeter to adjust and display the charge current level. HELVI AUTOSTAR500 is protected with internal fuse against short circuits or polarity reversal and thermostatic protection against prolonged starts. HELVI AUTOSTAR500 is equipped with C.P.S. (car protection system) able to activate and deactivate the start function (boost) totally automatically, to protect the electronics on board the vehicle.

The HELVI AUTOSTAR500 battery charger is perfect for charging batteries with a 12 V or 24 V voltage and a 36 A current.

The HELVI AUTOSTAR500 battery charger can charge batteries for various types of vehicles such as cars, vans, boats and tractors. The main applications of the HELVI AUTOSTAR500 battery charger are in the automotive, domestic and agricultural sectors.

HELVI AUTOSTAR500 is a single-phase battery charger with 230 V power supply and 50/60 Hz frequency. The HELVI AUTOSTAR500 battery charger has a rated power of 1300 W for a maximum current of 55 A.

The nominal charging capacity of the HELVI AUTOSTAR500 charger is 540 Ah and has 6 charging positions plus Boost.

HELVI AUTOSTAR500 is very compact and also light thanks to its weight of about 18 Kg.

Technical characteristics of the HELVI AUTOSTAR500 battery charger:

Phase type: Single-phase

Voltage: 230 V

Frequency: 50/60 Hz

Power: 1300 W

Battery voltage: 12/24 V

Maximum current: 55 A

Charging current: 36 A

Maximum surge current: 450 Acc



Charging capacity: 540 Ah 15h
Charging positions: 6 + Boost
Length: 345 mm
Width: 250 mm
Height: 280 mm
Weight: 18.3 Kg

If you are looking for another product similar to the HELVI AUTOSTAR500 portable charger, then we recommend that you take a look at the entire range dedicated to battery chargers.

Images and technical data are not binding.

Product features:

Phase: Single phase
Frequency (Hz): 50 / 60
Voltage (V): 230
Power (W): 1300
Adjustment positions: 6 + Boost
Nominal current (A): 36
Charge capacity (Ah): 540
Battery voltage (V): 12 / 24
Charging voltage (V): 12 / 24
Current max (A): 55
Length (mm): 345
Width (mm): 250
Height (mm): 280
Product type: Battery Charger
Weight (Kg): 18.3