



RIMOR VFR500 004G1 INVERTER SINGLEPHASE 4KW IP54

Product price:

630.03 € tax excluded

Product description:

INVERTER VFR500 004G1 SINGLEPHASE 4KW IP54

The inverter VFR500 004G1 of 4KW power with IP54 protection rating is a voltage and frequency converter capable of generating a voltage and frequency controlled three-phase system to make it possible to vary the speed of asynchronous or vector motors.

The Inverter VFR500 004G1 is equipped with a display for reading and programming with the possibility to activate a very large number of functions, to satisfy every industrial application.

The application of inverters to the various operating machines (pumps, fans, conveyor belts, mills, etc.) allows to obtain a real energy saving, as only the actual power needed is consumed. In fact, the starting by inverter is done by absorbing the actual necessary current, so it is not necessary to take into account the high inrush currents present in case of starting with other systems.

The 4KW inverter has an IP54 housing and is equipped with filters for cooling air inlet and outlet. This requirement allows

keep the internal inverter unit particularly clean, limiting the deposit of dirt on the heat sink, boards and internal components.

Therefore, the Rimor IP54 inverter is a simple, robust and reliable piece of equipment, containing the classic Rimor IP23 standard inverter inside, which is shielded and cooled in the most appropriate way. This solution guarantees reduced maintenance, longer life and greater reliability of the inverter.

The abbreviation IP corresponds to International Protection Rating and, following the IEC 60529 standard, identifies the degrees of shielded of the enclosures for electrical devices.

This standard was also created to avoid an excessive use of vague terms, such as "waterproof". Thanks to the IP protection class it is instead possible to be more exhaustive and precise, clearly



defining to what extent the device is shielded against the intrusion of solid and liquid bodies, dust and possible accidental contact.

TECHNICAL CHARACTERISTICS OF SINGLE-PHASE INVERTER VFR500 004G1 IP54

Input Voltage: 220V Working power: 4KW

Overload: 150%

Maximum output frequency: 500 Hz Min. operating temperature: -10.00 °C Max working temperature: 40.00 °C

Protection class: IP54

Length: 250 cm Width: 300 cm Height: 400 cm

If you are looking for an Inverter with other features or more power than 4KW then we suggest you to browse our wide <u>catalogue</u>

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power three phase (KW): 4

Voltage (V): 220 - 240 Protection degree: IP54 Length (mm): 2500 Width (mm): 3000

Height (mm): 4000

