



# GENMAC G1 MOTORPUMP CLEAN WATER



## Product description:

### GENMAC G1 MOTORPUMP SELFPRIMING FOR CLEAN WATER

The Motorpump **Genmac G1** is a selfpriming gasoline powered with a maximum flow rate of **133Lt/min** with air cooling suitable for any **clean water** application.

The Genmac selfpriming motorpump is suitable for emptying swimming pools, ponds, fountains or for irrigation, thanks to its light weight and compact size will be easy to use in any area will be intended..

The Genmac G1 engine has a cast iron cylinder barrel with excellent performance and highly reliable semi-professional quality, easy to start, ensures low noise and vibration with low consumption. Thanks to its only 13,5Kg and to the trolley equipped with wheels it is possible to re-launch it easily and effortlessly wherever it is needed.

The selfpriming Genmac motorpump has a maximum flow rate of 133Lt/min which makes it incredibly efficient due to its small and handy dimensions.

The Genmac **selfpriming motorpump** with a flow rate of 133Lt/min is part of a type of hydraulic centrifugal with over-beam installation. Therefore, like all such types of machines, it sucks in a higher level of the liquid to be pumped and therefore needs adequate priming in order to function correctly.

When the motorpump is started; the rotating movement of the impeller creates a strong turbulence in the liquid contained inside the motorpump body that generates a depression (up to 0.8 bar) inside the pipe that sucks the air contained in it.

## TECHNICAL CHARACTERISTICS MOTORPUMP GENMAC G1

Motor: R80-V



Type: 4-stroke, air cooling  
Fuel: Gasoline  
Displacement: 79 cc  
Tank capacity: 2 liters  
Autonomy: 2.5 hours  
Suction: 25 (1")  
Delivery: 25 (1")  
Suction capacity: 6 m  
Maximum head: 28 m  
Maximum flow rate: 133Lt/min  
Length: 375mm  
Width: 310 mm  
Height: 365 mm  
Weight: 13.5 Kg

Are you looking for a product with different characteristics or with a flow rate greater than 133Lt/min? [Here you can find](#) the full range of Genmac diesel and gasoline motorpumps or other specialized brands.

The images and technical data of the clean water motorpump are not binding and may be subject to revision by the supplier

**Product features:**

Fuel: Gasoline  
Starting system: Pull starter  
Pump type: Lightweight Pump  
Fluid type: Clean water  
Height of suction (m): 28  
Maximum output capacity (Lt/min): 133  
Inlet diameter thread type (mm/inches): 25 mm - 1"  
Outlet diameter thread type (mm/inches): 25 mm - 1"  
Fuel tank capacity (L): 12.5  
Length (mm): 375  
Width (mm): 310  
Height (mm): 365  
Dry weight (Kg): 13

