



GENMAC Combi RG4000HO-M5 GENERATOR 3,4KVA

Product price:

784.00 € tax excluded

Product description:

GENMAC Combi RG4000HO-M5 GENERATOR 3,4KVA

The generator Genmac Combi RG4000HO-M5 single phase has a GP200 4 strokes Stage V gasoline powered engine capable of delivering a power of 3,4KVA with the possibility of connection to optional AVR.

The Genmac RG4000HO-M5 single phase generator is equipped with a Honda engine powered by gasoline with a tank capacity of 16 liters for an autonomy of about three and a half hours, complete with manual recoil starter.

The Genmac 3,4KVA generator is portable of professional quality and you can ask for the supply with AVR.

Optional AVR regulator

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

The series of Combi generators has been designed according to the standards, for mobile use, with the possibility to have on customer's specific request the handling kit designed exclusively for the selected product.

Technical features of generator 3,4KVA Genmac Combi RG4000HO-M5



Power supply: Gasoline Phase type: Single phase

Continuous power: 2.9KVA / 2.6KW Maximum power: 3,4KVA / 3,1KW

Voltage: 230V Frequency: 50 Hz

Engine: GP200 4 strokes Emission regulation: Stage V

3000 rpm Tank: 16 Lt.

Autonomy @ 75%: 13 h fixed rpm

Starting: Manual Length (mm): 620 Width (mm): 430 Height (mm): 430 Dry weight (Kg): 52

If you are looking for another product then you can consult on our catalog other generator

Images and technical data are not binding and may be subject to review

Product features:

Phase: Single phase

Maximum power single phase (KW): 3.1 Continuous power single phase (KW): 2.6 Maximum power single phase (KVA): 3.4 Continuous power single phase (KVA): 2.9

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230 Engine: 4 stroke

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Starting system: Pull starter

Cooling: Air

Fuel tank capacity (L): 16
Running time (h): 13
Length (mm): 620
Width (mm): 430
Height (mm):



Dry weight (Kg): 52

Product type: Generator ATS Switch device : No

Voltage regulator: AVR (optional)

