



# GENMAC Combi RG5000HEO-M5 GENERATOR 5,1KVA

Product price:

**1,360.00 € tax excluded**

## Product description:

### **GENMAC Combi RG5000HEO-M5 GENERATOR 5,1KVA**

The generator Genmac Combi RG5000HEO-M5 single phase has a Honda GX270 Stage V gasoline powered engine capable of delivering a power of 5,1KVA with the possibility of connection to optional AVR.

The Genmac RG5000HEO-M5 single phase generator is equipped with a Honda engine powered by gasoline with a tank capacity of 5,3 liters for an autonomy of about three and a half hours, complete with manual recoil starter.

The series of Combi generators has been designed according to the standards, for mobile use, with the possibility to have on customer's specific request the handling kit designed exclusively for the selected product.

The Genmac 5,1KVA generator is portable of professional quality and you can ask for the supply with AVR.

### **Optional AVR regulator**

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

Technical features of generator 5,1KVA Genmac Combi RG5000HEO-M5



Power Supply: Gasoline  
Boosting: Electronic  
Phase Type: Single Phase  
Continuous Power: 4.4KVA / 4.0KW  
Maximum Power: 5.1KVA / 4.6KW  
Motor: Honda GX270  
Emission Standard: Stage V  
Voltage: 230V  
Frequency: 50 Hz  
3000 rpm  
Fuel tank: 16 Lt.  
Run time @ 75%: 10 h fixed rpm  
Sound pressure: 72 dB (A) @ 7m  
Starting: Manual  
Length (mm): 740  
Width (mm): 500  
Height (mm): 530  
Dry weight (Kg): 80

If you are looking for another product then you can consult on [our catalog](#) other [terrestrial generator](#).

Images and technical data are not binding and may be subject to review

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 4.6  
Continuous power single phase (KW): 4.0  
Maximum power single phase (KVA): 5.1  
Continuous power single phase (KVA): 4.4  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Engine: Honda GX270  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Cooling: Air  
Fuel tank capacity (L): 16  
Running time (h): 10

---



Shop name

---

Acoustic pressure: 72 dB(A) at 7 m

Length (mm): 740

Width (mm): 500

Height (mm): 530

Dry weight (Kg): 80

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR (optional)



PrestaShop